			WATER '	WELL R	ECORD	Form W	WC-5 KS	SA 82a-12	212		
1 LOCATION	OF WATE	R WELL:	FRACTION			SEC	CTION NUMBER	TOWNSH	IIP NUMBER	RANGE N	JMBER
Sedgw			NW 1.	·	1/4 NV	W 1/4	25	Т	27 s	R 21	E/W
			r city street address of		within city?						
	tagecoa		<u>Wichita,</u> EWIS, Jo Lyn								
RR#,ST. A			040 Stagecoach						Board of Agr	iculture, Division of V	Vater Resource
7 11 11/10 17 1			ichita, Kansa			;	ZIP CODE:		Application Nur	nber:	
3 LOCATE	WELL'S LO	CATION	4 DEPTH OF CO	MPLETED V	WELL:	80 ft.		ELEVATION:			
WITH AN	"X" IN SEC	TION BOX:	Depth of groundwa	iter Encount	tered:	1	ft.		ft.		ft.
	1 1		WELL'S STATIC	WATER LE\	/EL 14	FT. BEL	OW LAND SUI	RFACE MEAS	SURED ON mo/	day/yr: 7/12	2/16
	, ,w, - -	-NE		Pump test d	ata: Well	water was		ft. after	hours	s of pumping @	gpr
<u>≅</u> w		1	Est. Yield:	gpm		water was		ft. after	hour	s of pumping @	gpn
≥ ₩	1	E	Bore Hole Diame	_	2 in.	to	80 ft.	and	in.	to	ft.
\\[\]	3W -	- SE	WELL WATER TO 1. Domestic	3. Feedlot		water supply	7. Lawn a	nd garden or	9. Dewateri	9	ction well
	1	: 1	2. Irrigation	4. Industria			ly 8. Air cond		 10. Monitori	12. Other (S _i ng well	pecify below
│	S		Was a chemical/ba	cteriological sa			YES	NO		what mo/day/yr v	•
<u></u>			submitted				Was W	ater Well Dis	nfected?	\geq	NO
<u> </u>	E OF CAS Steel	ING USED: 3. RPM	1 (SR) 5. Wrou	ght Iron	7. Fibergla	ass 9. (Other (Specify	below) CA	SING JOINTS:	Glued	Threaded
	PVC) 4. ABS		tos-Cement	8. Concre	_{te tile} SI	PR-26			Welded	Clamped
Blank casir			in. to	40 ft	t., Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing hei	oht above	land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall	thickness or gau	ge No214	
_	_		 ΓΙΟΝ MATERIAL:					*****	unoooo or goo	.214	
1. Steel	3	. Stainless Ste	el 5. Fibergla	ss (7. PVC	9.	ABS	11. (Other (specify)		
2. Brass	4	. Galvanized	Concret	e Tile	8. RMP (S	R) 10.	Asbestos-Cem	ent 12. N	lone used (open	hole)	
SCREEN O	R PERFO	RATION OPE	NINGS ARE:								
1. Contin	uous slot	3. M i	ili slot	5. Gauzed v	vrapped	7. T	orch cut	9. Dr	illed holes	11. Nопе (с	pen hole)
2. Louver	ed shutte	r 4. Ke	y punched	6. Wire wra	pped	8. S	aw cut	10. Ot	her (specify)		
SCREEN - F	PERFORA	TION INTERV	AL From	40	ft.	to 80	ft.,	From	ft.	to	ft.
			From		ft.	to	ft.,	From	ft.	to	ft.
GR	AVEL PA	CK INTERVAL	S: From	24	ft.	to 80	ft.,	From	ft.	to	ft.
			From		ft.	to	ft.,	From	ft.	to	ft.
6 GROU	T MATERI	ALS: 1. N	eat cement	2. Cei	ment Grout		3. Bentonite			tonite hole pl	
Grout In	tervals:	From		to 24	ft., Fro	m f	-	ft.,	From	ft. to	− ft.
1		•	le contamination:	7 Pit priva	v	10. Livesto	ck pens			15 Oil well/C	ese wall
1	1. Septic tank 4. Lateral lines 7. Pit privy 2. Sewer lines 5. Cass Pool 8. Sewage lagoon						•	 13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below 			
2. Sewer			ss Pool	_	-	11. Fuel st	•	14. ADan	don water well		,
3. Watert	ight sewe	r line 6. Se Northea	epage pit ast	9. Feed ya	ıru	12. Fertiliz	er storage	How r	nany feet? 40	ft. nlus	
From	To	110101101	LITHOLOG	SIC LOG		From	То	110111		OGIC LOG	
0	3	topsoil									
3	10	clay									
10	75	grey shale					_				
75	80	limestone					+			<u> </u>	
									···		
<u> </u>											
7 Contra	actor's or l	andowner's C	ertification: This wa		1. construc	ted 2. 1	econstructed	or 3.	plugged	under my jurisdict	ion and
was com	pleted on	(mo/day/year)	7/12/10)	and this rec	ord is true to the	ne best of my k	nowledge and	d belief.		
Kansas V	Vater Well	Contractor's L	icense No. 236		This wate	r well record v	vas completed	on (mo/day/ye	ear) 7 /1	13/16	
under the	business	name of Ha	rp Well and P	ump Ser	vice	by (signature)	7	odd.	. Harp)
1			-	-						, itom p	•