		WATER WE	ELL RECO	RD Fo	rm WW	/C-5 K	SA 82a-12 ⁻	12		
1 LOCATION OF WATE	R WELL:	FRACTION				ION NUMBER	1	NUMBER	RANGE N	
Sedgwick		SE 1/4	NE 1/4		1/4	26	Т 2	7 S	R 21	C E/W
Distance and direction from	-									
14227 E. Spri			chita, Kans	as						
2 WATER WELL O		CHER, Tony						Board of Agri	culture, Division of V	Vater Resource
RR#,ST. ADDRESS		9 Willowcreek	Circle					board of Agri	calcare, Division of v	valer Nesource
CITY,		nita, Kansas			ZIF	P CODE:		Application Num	nber:	
3 LOCATE WELL'S LO		DEPTH OF COMPL	ETED WELL:	86	ft.		ELEVATION:			
WITH AN "X" IN SEC	Dep	pth of groundwater	Encountered:		ft.			ft.		ft.
	WE	ELL'S STATIC WA	TER LEVEL	14	T. BELO	W LAND SU	IRFACE MEASU	JRED ON mo/o	lay/yr: 7/1 1	l/ 16
NW	NE	Pum	np test data:	Well water	was		ft. after	hours	of pumping @	gpm
1 (1	145	Est. Yield:	gpm	Well wate			ft. after		of pumping @	gpm
₩ Z w	Е В	ore Hole Diameter	12 ir	١,	to 8	6 ft.	and	in.	to	ft.
=	Iwi	ELL WATER TO BE						9. Dewateri	na 11. lnje	ction well
sw -	SE	. Domestic 3. I	Feedlot 5. I	Public wate	r supply '	7. Lawn a	ind garden only		•	pecify below)
	2	2. Irrigation 4. I	ndustrial 6.	Oil field wat	ter supply	8. Air con	ditioning	10. Monitorir	-	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		Vas a chemical/bacteri	ological sample su	ibmitted to De	partment?	YES	NO		what mo/day/yr v	
		bmitted				Was V	Vater Well Disin	fected?	YES	NO
5 TYPE OF CAS	_	5. Wrought I	ron 7. F	iberglass	9. Ot	her (Specify	below) CAS	SING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SF	≺) 6. Asbestos	Compat 8 (Concrete tile	SDF	R-26			Welded	Clamped
2. PVC	> 4. ABS									
Blank casing diameter	er 5		15 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above	e land surface:	12 in.,	W	eight: 2	.35 lb	os. / ft.	Wall th	ickness or gaug	ge No214	
TYPE OF SCREEN	OR PERFORATION	N MATERIAL:		_						
1. Steel	3. Stainless Steel	Fiberglass	(7. P	vc)	9. A	BS		her (specify)		
2. Brass	I. Galvanized	Concrete Ti	le 8. R	MP (SR)	10. As	sbestos-Cer	nent 12. No	one used (open	hole)	
SCREEN OR PERFO	RATION OPENING	GS ARE:								
1. Continuous slo	3. Mill sl	ot 5. G	auzed wrappe	d	7. Tor	rch cut	9. Dril i	led holes	11. None (open hole)
2. Louvered shutte	er 4. Key pı	unched 6 W	ire wrapped		(8. Sa)	w cut	10. Oth	er (specify)		
		unoneu o. v.	• • •		_			(,		
SCREEN - PERFORA	ATION INTERVAL	From	45 ft.	to	86	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PA	CK INTERVALS:	From	24 ft.	to	86	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
G GROUT MATER	IAI S. A. N A.		2.6	4		Doutouite				
The state of the s									•	
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to What is the nearest source of possible contamination:								ft.		
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage						15. Oil well/0	Gas well			
8 Sewage laggon 11 Fuel storage 14 Abandon water well 16. Other (specify bel								pecify below)		
2. Sewer lines 5. Cess Pool 6. Sewage ragoon 11. Total storage 14. Abandon water well 14. Abandon water										
Direction from well?	South	ige pit	,				How m	any feet? 20 f	ft. plus	
From To		LITHOLOGIC	LOG		From	То			GIC LOG	
0 3	topsoil	2,,,,,,,,,,			7.0111		1	2	0.0 200	
3 20	clay									
20 35	brown shale									
35 86	grey shale									
									-	
	_									
	<u> </u>									
	 									
	†									
7	Landau and America	lastina Tita			\		4 05 0	nlugged	under my instact	tion and
7 Contractor's or	Landowner's Certifi		well was 1. Co	nstructed	2. re	constructed	d or 3.	plugged	under my jurisdic	uon and
was completed on	(mo/day/year)	7/11/16	and t	his record is	true to the	best of my	knowledge and	belief.		
Kansas Water Wel	l Contractor's Licen	se No. 236	Th	is water well	record wa	s completed	on (mo/day/yea	ar) 7 /1	3/16	
under the business name of Harn Wall and Pump Services by (signature)										
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										