1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212	1		
		3777 379		Section Number	Township Number	Range Number	
Sedgwick	SE 1/4	NW 1/4 N	W 1/4	8	T 27 s	R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city?							
1/4 E. of Rock Rd., 1/4 S. of 21st Wichita, Kansas water well owner: RITCHIE DEVELOPMENT							
WATER WELL OWNER: RITCHIE DEVELOPMENT RR#, ST. ADRESS, BOX #: 8100 E. 22nd N. Board of Agriculture, Divivsion of Water Resource							
		- · · · · · · · · · · · · · · · · · · ·					
	ta, Kansa DEPTH OF COM		65	ft. ELE	Application Number	•	
AN HYE DI SECTION BOY.	DEF III OF COM Depth(s) groundwa		1	it. ELE ft.	2 ft.	3 ft.	
A		ATER LEVEL 10	_		RFACE MEASURED ON mo/day/yr	08/14/1998	
	Pump test	<u>.</u> .	ater was				
NE NE	Yield		ater was		after hours pum after hours pum		
=	e Hole Diameter		o 65	ft.	and in.	ping gpm to ft.	
E WE	LL WATER TO B		Public water			ajection well	
	1 Domestic		Oil field wat		•	ther (Specify below)	
	2 Irrigation		Lawn and ga		0 Monitoring well	(1)	
$ \downarrow _{\mathbf{W_a}}$	ū			·	•	o/day/yr sample was	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement		Other (Specify b		elded A Clamped	
2 PVC 4 ABS		7 Flberglass	-	OR-26	•	hreaded	
Blank casing Diameter 5 in.	to 20	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12	in.,	welght 2.			Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify)	
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (op	en hole)	
SCREEN OR PERFORATION OPENIN	5 Gauze	5 Gauzed wrapped		8 Saw cut 11 None (open hole)			
1 Continous slot 3 Mill slot		6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4 Key punch	ed	7 Torch	cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 20 ft. to 65 ft., From ft. to ft.							
	from	ft. 1		ft., From		ft.	
GRAVEL PACK INTERVALS: from 24		ft. to 65		ft., From		ft.	
	from	ft. 1		ft., From		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
Crout Intervals: From A 4 4 2 A					ft. to ft.		
What is the nearest source of possible contamination:				10 Livesto	•	bandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy	7 Pit privy		orage 15 C	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon				16 Other (specify below)	
3 Watertight sewer lines 6 Seepage 1	9 Feedyard		13 Insecticide storage				
Direction from well? South How many feet? 100							
	HOLOGIC LOG		FROM	TO	PLUGGING INTER	RVALS	
0 4 topsoil							
4 8 clay				 		****	
8 40 shale			 				
40 65 limestone			-	 -			
			 	 			
			 	+			
				 			
			†				
		·	 	 			
				 			
				1			
				<u> </u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION. This water well was (1) constructed (2) reconstructed or (3) plugged under my jurisdiction and							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Well Contractor's License No236							
Under the business name of Harp. Well & Pump. Service. Inc. by (signature)							
Todd S. Harp							