1 LOCATION OF WATER WELL:			FRACTION	Water W	ell Record 1	Form WWC-:	KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick			SW 1/4	SW 1/	4 NW	1/4	8	27	2₽	
Distance and direction frem nearest town or city street address of well if located within city?										
1830 Saddlecreek Circle Wichita, Kansas										
WATER WELL OWNER: HEATHERLY, Tony										
RR#, ST. ADRESS, BOX #: 1830 Saddlecreek Circle Board of Agriculture, Divivsion of Water Resource										
CITY, STATE, ZIP CODE: Wichita, Kansas  Application Number:									:r:	
	TE WELL'S	LOCATION WITH 4	DEPTH OF CO	OMPLETED W	VELL	50	ft. ELE	VATION:		
AN "X	" IN SECTIO	N	Depth(s) ground			1	ft.	2 ft.	3 ft.	
H			ELL'S STATIC		EL 5	FT.	BELOW LAND SUF	RFACE MEASURED ON mo/day/yr	05/29/1998	
'	NW-	NE	-	est data:	Well wate		ft.	after hours pum	iping gpm	
ا ا	<b>k</b> :		. Yield	gpm: r 12	Well wat			after hours pum	. o ar	
M Mile	/ <del></del>	1 1 1 1 1 1 1	e Hole Diamete LL WATER T	=	in. to		ft.	and in.	to ft.	
			LLL WATER IN	3 Feedlot		ıblic wate il field wa		· ·	njection well Other (Specify below)	
	sw	SIE	2 Irrigation	4 Industria				O Monitoring well	ther (Speerly below)	
]	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample submitted to Department?								10/dav/vr sample was	
S submitted Water Well Disinfected? Yes X No										
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Stee	el	3 RMP (SR)					Other (Specify be	ther (Specify below) Welded		
2 PV		4 ABS		7 Fibergla:	SS	S	DR-26	Т	`hreaded	
	asing Diar		to 24	,	Dia	in.	to	ft., Dia in.	to ft.	
		ve land surface 12 EN OR PERFORATIO	in. N Materiai	, we	eight 2.3			Wall thickness or gauge No. 10 Asbestos-ceme	.214	
1 Ste		3 Stainless Steel	MATERIAL	5 Fiberglass	s		PYC RMP (SR)	11 other (specify		
2 Bra		4 Galvanized steel		6 Concrete			ABS	12 None used (or	•	
SCREE	N OR PE	RFORATION OPENI	NG ARE:		5 Ganzed	_		8 Saw cut	11 None (open hole)	
1	nous slot	3 Mill slot			5 Gauzed wrapped 6 Wire wrapped			9 Drilled holes		
2 Louve	red shutte	er 4 Key punch	ied		7 Torch cu			10 Other (specify)		
SCREE	N-PERFO	RATION INTERVAL	S: from 2		ft. to		ft., From	ft. to	ft.	
			from		ft. to		ft., From		ft.	
GRAVEL PACK INTERVALS: from 24				4	ft. to 50		ft., From		ft.	
<u> </u>		· · · · · · · · · · · · · · · · · · ·		ft. to		ft., From		ft,		
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentontite hole plug Grout Intervals: From 4 ft. to 24 ft. From 6 to 6										
			. to 24	ft. From	m	ft.		ft. From	ft. to ft.	
What is the nearest source of possible contamination:  1 Septic tank  4 Lateral lines				7 Pit r	7 Pit privy		10 Livestoo 11 Fuel sto	- 11.12 - 11.12	14 Abandon water well	
			=	8 Sewage lagoon			130	15 Oil well/Gas well 16 Other (specify below)		
2 <u>Sewer lines</u> 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify bel 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								other (specify below)		
Direction from well? East How many feet? 30										
FROM TO LITHOLOGIC LOG				G	FROM			TO PLUGGING INTERVALS		
0 4	4	topsoil								
4 30	30	soft shale								
35	35 50	coarse shale	<u> </u>				<u> </u>			
-	30	TIMESCORE								
				·	-					
			. 1979	· · · · · · · · · · · · · · · · · · ·						
					1				· · · · · · · · · · · · · · · · · · ·	
				····						
		-		<del></del>						
<b>—</b>										
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)										
Cilder	under the dusiness name ofby (signature) dodd d. flarp									