Troc	ATTON OF W	A TERR SHELL	EBACTION		Well Record F	orm WWC-5	KSA 82a-1212		····	
الماليا	ATION OF W Sedgw	'ATER WELL:	FRACTION NE		1/4 NW		Section Number	Township Number	Range Number	
Distance						1/4		T 21 S	R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city? 21st N. & Webb, 1/4 East, 200 yds South Wichita, Kansas										
WATER WELL OWNER: INVESTMENT RESOURCES										
RR#,	, ST. ADRESS	S, BOX #: 7700	E. Kellog	3 g				Board of Agriculture	, Divivsion of Water Resource	
	Y, STATE, ZI		ta, Kansas Application Number					ber:		
	ATE WELL'S K" IN SECTIO	DOCKETOR WILL		COMPLETED		112		EVATION:		
1	TT	N		undwater Encour		1	ft.	2 ft.	3 ft.	
	7			FIC WATER LEV	VEL ⊥⊃ Well wate		BELOW LAND SI	URFACE MEASURED ON mo/day/yr after hours pu		
, ,	— - NW-	NE	Est. Yield	gpm:	Well wate		π. ft.	after hours pu		
ĭ ĭije	<u>، ا</u>		Bore Hole Diam	0.	in. to		ft.	and in	- 0	
=			WELL WATER	R TO BE USED A	.S: 5 Pu	ıblic water	·supply	8 Air conditioning 11	Injection well	
	- sw-		1 Domestic			il field wat		ŭ	Other (Specify below)	
	1		2 Irrigation		· 		arden only	10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample										
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Stee		3 RMP (SR)			nt iron os-Cement		Concrete tile Other (Specify)		Welded A Clamped	
2 PV	C	4 ABS		7 Fibergla			R-26	Dela,	Threaded	
Blank c	asing Diar	neter 5	in. to 30	ft. ,	Dia	in.	to	ft., Dia in.	to ft.	
	U	ove land surface 12			veight 2.35		lbs. / ft.	Wall thickness or gauge No.	.214	
1		EN OR PERFORAT	ΓΙΟΝ MATERI	AL: 5 Fiberglas			PVC RMP (SR)	10 Asbestos-cei		
1 Ste 2 Bra		3 Stainless Steel 4 Galvanized stee	A)	6 Concrete			ABS	11 other (speci	• *	
		RFORATION OPE	-	0 00			ADS	12 None used (8 Saw cut	open hole) 11 None (open hole)	
	inous slot	AFORATION OF E 3 Mill slo			5 Gauzed v 6 Wire wra			9 Drilled holes	11 Hone (open now,	
	ered shutte				7 Torch cut			10 Other (specify)		
SCREE	N-PERFO	RATION INTERV			ft. to		ft., Froi		ft.	
			from		ft. to		ft., Froi		,	
	GRAV	EL PACK INTERV	VALS: from	24	ft. to	112	ft., Fro			
<u> </u>			from		ft. to				o ft.	
	OUT MAT ntervals:	ERIAL: 1 Neat c		2 Cement ground		3 Bent	tonite	4 Other bentonite	hole plug	
		From 4 st source of possible	ft. to 24	ft. Fro	m	ft. te	o 10 Livesto	ft. From	ft. to ft.	
	tic tank	4 Latera			privy	11 Fuel storage			Abandon water well i Oil well/Gas well	
2 Sewer lines 5 Cess p				00					16 Other (specify below)	
3 Wate	ertight sew	-	-	9 Fee	9 Feedyard			13 Insecticide storage None Apparent		
Direction from well?										
FROM 0			LITHOLOGIC I	JOG		FROM	ТО	PLUGGING INT	ERVALS	
4	30	topsoil clay	-				 			
30	50	shale	VA				+ +			
50	112	limestone	with stre	aks of sha	le		1			

<u> </u>	 				\longrightarrow		 			
							 			
	 				-		 			
 	 						 			
	 						 			
	<u> </u>		7.0							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and										
was completed on (mo/day/year)06/17/1998 and this record is true to the best of my knowledge and belief. Kansas										
Water Well Contractor's License 13.6										
Under the business name ofby (signature) $Jodd$ $\&$. $\mathcal{H}arp$										