

1	LOCATION OF WATER WELL:	Fraction	NW	1/4	NW	1/4	SW	1/4	Section Number	T	27	S	R	2	Range Number	County:	SEDGWICK
---	-------------------------	----------	----	-----	----	-----	----	-----	----------------	---	----	---	---	---	--------------	---------	----------

2 WATER WELL OWNER: RAYTHEON AIRCRAFT CO RR# St. Address, Box #: 9707 EAST CENTRAL WICHITA, KS 67206 Board of Agriculture, Division of Water Resources Application Number:	1/2 MILE NORTH OF 13TH ST ON GREENWICH RD. WICHITA, KS SAL MW# 11AI Distance and direction from nearest town or city street address of well if located within city?
--	---

LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL

ft. ELEVATION: 45

1. ft. 2. ft. 3.

WELL'S STATIC WATER LEVEL

ft. below land surface measured on mo/day/yr

Pump test data: Well water was

Est. Yield

Bore Hole Diameter

AS TO BE USED AS:

1 Domestic

2 Irrigation

3 Feedlot

4 Industrial

5 Public water supply

6 Oil field water supply

7 Lawn and garden only

8 Air conditioning

9 Dewatering

10 Monitoring well

11 Injection well

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes

Water Well Disinfected? Yes

No

AN "X" IN SECTION BOX:

LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL

1. ft. 2. ft. 3.

WELL'S STATIC WATER LEVEL

ft. below land surface measured on mo/day/yr

Pump test data: Well water was

Est. Yield

Bore Hole Diameter

AS TO BE USED AS:

1 Domestic

2 Irrigation

3 Feedlot

4 Industrial

5 Public water supply

6 Oil field water supply

7 Lawn and garden only

8 Air conditioning

9 Dewatering

10 Monitoring well

11 Injection well

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes

Water Well Disinfected? Yes

No

TYPE OF BLANK CASING USED:					
5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . . . Clamped . . .			
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded . . . Threaded X . . .	
X2 PVC	4 ABS	7 Fiberglass			
Blank casing diameter	2 in. to 3.5 ft. Dia.	in. to	ft., Dia.	in. to	ft.
Casing height above land surface.	0 in., weight	sched 40	lbs./ft. Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	8 Saw cut
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	X 3 Mill slot	0.10	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut		5 Gauzed wrapped	10 Other (specify)
SCREEN-PERFORATED INTERVALS:					
From	ft. to	3.5	ft., From	ft. to	ft.
45	ft. to	3.2	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:					
From	ft. to	4.5	ft., From	ft. to	ft.

[illegible]

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	DARK BRN SILTY CLAY			
1	2.5	YELLOW BRN SILTY CLAY			
2.5	9	DARK GREY SILTY CLAY			
9	13	YELLOW BRN SILTY CLAY			
13	15	YELLOW BRN SILTY CLAY			
15	17	MOTTLED DARK BRN SILTY CLAY			
17	20	CLAYEY SILT			
20	25	DARK GREYISH BRN SILTY CLAY			
25	26	SILTSTONE & SILTY CLAY PALE YELLOW			
26	34.5	LIGHT OLIVE BRN SILTY CLAY			
34.5	39	DARK OLIVE GREY SILTY CLAY			
39	39.5	SILTSTONE			
39.5	45	DARK OLIVE BRN SILTY CLAY			