1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212			
			_	Section Number			Range Number
Sedgwick NE 1/4		SE 1/4 SV	1/4	11	T 27 s		R 2E E/W
Distance and direction frem nearest town or city street address of well if located within city?							
13311 Edgewood (Edgewood & Glennwood) Wichita, Kansas							
KIICHIE ADDOCIAIED INC.							
RR#, ST. ADRESS, BOX#: 8100 E. 22nd N CITY, STATE, ZIP CODE: Wichita, Kansa				68006	Board of Agriculture, Divivsion of Water Resource		
	······				tion Number	•	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COM Depth(s) groundwa		87	ft. E ft.	LEVATION:		3 ft.
	Depui(s) groundwa ELL'S STATIC WA		1		2 ft SURFACE MEASURED ON m		3 ft. 07/16/1998
	Pump test						
NW	. Yield		iter was	ft. ft.		urs pump urs pump	
e Po	re Hole Diameter 니			ft.	and	in.	oing gpm to ft.
E W	ELL WATER TO B		Public water		8 Air conditioning		jection well
1.	1 Domestic		Oil field wate		9 Dewatering		ther (Specify below)
SW X	2 Irrigation	4 Industrial 7	Lawn and ga	rden only	10 Monitoring well	win	ndmill
	as a chemical/bacte	riological sample subi	mitted to Dep	partment? Ye	s No ;		o/day/yr sample was
S submitted Water Well Disinfected? Yes No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)	6 Asbestos-Cement	Trought from Control the Control of the 21 Champes					
2 PVC 4 ABS		7 Fiberglass				Tì	hreaded
Blank casing Diameter 6 in.	. to	ft., Dia	in.	to	ft., Dia	in.	to ft.
Casing height asset land surface 60	in.,	weight		lbs. / ft.	Wall thickness or gauge		
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless Steel	5 Fiberglass					N/A	
2 Brass 4 Galvanized steel	6 Concrete tile				used (ope	,	
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped		8 Saw cut 11 None (open hole)			
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N/A							
SCREEN-PERFORATION INTERVAL	S: from	ft. t	0	ft., Fr	o m	ft. to	ft.
from		ft. t	0	ft., Fr	o m	ft. to	ft.
GRAVEL PACK INTERVALS: from		ft. (to ft., Fron		om	ft. to	ft.
from ft. to ft., From ft. to					<u>ft.</u>		
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
Grout Intervals: From 3 ft. to 10 ft. From ft. to ft. From 10 ft. to 30 ft. What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines				1 14 7.00		bandon water well	
					131		il well/Gas well
o coss poor			9 Feedvard 13 Insecticide storage			16 Other (specify below)	
None Apparent							
FROM TO LITHOLOGIC LOG			FROM	то	How many feet? PLUGGIN	C INTER	VALS
			0	3	topsoils	GINIER	VALS
			3	10	cement grou	t	
			10	30	bentonite h		olug
			30	87			d and gravel
				<u> </u>			
					 		
				<u> </u>			
				l			
OONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Well Contractor's License No236							
The Dushiess Hailie VI.ARMA.	p	***************************************		wy (31	Jad	'd. &	Harp