TOGETHOU OF THE TERM		I ED ACTION	Water Well Re	cord Form WWC-				
1 LOCATION OF WATER WELL:		FRACTION			Section Number	Township Number	Range Number	
Sedgwick		SE 1/4	SW 1/4	SW 1/4	11	т 27 s	R 2E E/W	
Distance and direction frem nearest town or city street address of well if located within city?								
1/4 E. of 127th E., 80' N. of 13th Wichita, Kansas								
WATER WELL OWNER: RITCHIE DEVELOPMENT								
RR#, ST. ADRESS, BOX#: 8100 E. 22nd N. Board of Agriculture, Divivsion of Water Resource								
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:								
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:								
AN "X" IN SECTION BOX:			ater Encountered	- •	ft.	2 ft.	3 ft.	
1 1 1		, .	ATER LEVEL	_		FACE MEASURED ON mo/day/yr	08/14/1998	
	WE	Pump test	_					
NW	NE	-		ll water was		fter hours pum	· ·	
<u>a</u>		Yield	91	ll water was		fter hours pum		
W Wile	; [2]	Hole Diameter	12 in.	to 80	ft.	and in.	to ft.	
	i I I	LL WATER TO		5 Public water		•	njection well	
sw	SAE	1 Domestic	3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation	4 Industrial	7 Lawn and	garden only 10	Monitoring well		
] + <u> </u>	Was	a chemical/bacte	riological sample	submitted to D	epartment? Yes	No X; If yes, m	o/day/yr sample was	
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING	USED:		5 Wrought iro	n 8	Concrete tile	CASING JOINTS: G	lued X Clamped	
						her (Specify below) Welded		
2 PVC 4 ABS 7 Fiberglass SDR - 26 Threaded							hreaded	
Blank casing Diameter	5 in.	to 35	ft., Dia	in.		ft., Dia in.	to ft.	
Casing height above land	-	in.,	•			Vall thickness or gauge No.	.214	
Casing height above land surface 12 in., weight 2.35 TYPE OF SCREEN OR PERFORATION MATERIAL:					7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify))	
2 Brass 4 Galvanized steel 6 Concrete tile					9 ABS 12 None used (open hole)			
					PG			
l				auzed wrapped	wrapped			
1 Continous slot	3 Mill slot		6 W	ire wrapped		9 Drilled holes		
2 Louvered shutter	4 Key punche	ed	7 To	rch cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 35 ft. to 80 ft., From ft. to							ft.	
from				ft. to		ft. to	ft.	
GRAVEL PACK INTERVALS: from 24			ft. to 80		ft., From	ft. to	ft.	
from				ft. to	. to ft., From		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals: From 4 ft. to 24 ft. From					to	ft. From	ft. to ft.	
What is the nearest source of possible contamination:					10 Livestoc		bandon water well	
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel stor	rage 15 (15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilize		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit			9 Feedvard	9 Feedyard 13 Insecticide storage			(1,	
Direction from well? South How many feet? 30								
FROM TO		FROM	то	PLUGGING INTE	RVALS			
	psoil	IOLOGIC LOG						
4 15 cla								
	ale							
	mestone							
			. ,					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No236								
Under the business name of Harp. Well & Pump. ServiceInc by (signature)								
Todd S. Harp								