WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER LOCATION OF WATER WELL: FRACTION NW 1/4 Sedgwick NESE 1/4 12 27 2EDistance and direction from nearest town or city street address of well if located within city? 15506 E. Summerfield Wichita, Kansas SHELTON, Greg WATER WELL OWNER: Board of Agriculture, Division of Water Resource 15506 E. Summerfield RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE Application Number 116 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION** WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered: 55 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/24/16 Pump test data: Well water was ft. after hours of pumping @ apm NW NE ft. after hours of pumping @ Est. Yield: gpm Well water was gpm Ē Bore Hole Diameter 12 to 116 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 1. Lawn and garden only SW SF 3. Feedlot 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO (YES) Was Water Well Disinfected? submitted TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 50 Dia. Blank casing diameter Dia in. ft. to 12 2.35 in . Weight: lbs / ft Wall thickness or gauge No. .214 Casing height above land surface: TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2 Brass 4 Galvanized SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7: Torch cut 8. Saw cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 10. Other (specify) 50 116 SCREEN - PERFORATION INTERVAL ft., From to ft ft. From to ft., From to ft. 24 **GRAVEL PACK INTERVALS:** ft. to 116 From ft., From ft. ft. to ft., From ft ft to **GROUT MATERIALS** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. 24 ft ft. From ft. to What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line South How many feet? 15 ft. plus Direction from well? LITHOLOGIC LOG From Τo LITHOLOGIC LOG From Tο 3 topsoil O clay 20 20 116 gray shale

7 Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/24/2016 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/26/2016

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp