Form WWC-5 WATER WELL RECORD KSA 82a-1212 FRACTION SECTION NUMBER TOWNSHIP NUMBER LOCATION OF WATER WELL: RANGE NUMBER NWNE SW Sedgwick 1/4 12 27 2E Distance and direction from nearest town or city street address of well if located within city? 15410 E. Summerfield Wichita, Kansas WATER WELL OWNER: LEEWOOD HOMES Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 3500 N. Rock Road CITY, STATE: Wichita, Kansas ZIP CODE: Application Number 116 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ELEVATION: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. 38 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/24/16 Pump test data: Well water was ft. after hours of pumping @ gpm NW NE Est. Yield: Well water was apm ft. after hours of pumping @ gpm ₫ Bore Hole Diameter 12 to 116 and ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample (NO Was a chemical/bacteriological sample submitted to Department? YES submitted Was Water Well Disinfected? TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 40 Dia. Blank casing diameter ft. in to 12 2.35 Casing height above land surface: in.. Weight: lbs. / ft. Wall thickness or gauge No .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9 ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut SCREEN - PERFORATION INTERVAL 40 116 to ft., From ft. ft. to ft to From ft., From ft. to 24 ft. GRAVEL PACK INTERVALS: to 116 From ft., From ft. From ft. to ft., ft. to ft **GROUT MATERIALS** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From ft 24 ft.. ft ft., to From ft What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit South Direction from well? How many feet? 10 ft. plus From Τо LITHOLOGIC LOG From То LITHOLOGIC LOG topsoil 20 clav 20 50 brown shale 116 gray shale

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/24/2016 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/26/2016

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp