WATER WELL RECORD F	orm WWC-5 K	(SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBE		RANGE NUMBER
Sedgwick SE 1/4 SW 1/4 NE	1/4 11	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?			
13905 E. Rock Hill Wichita, Kansas 2 WATER WELL OWNER: NIES CONSTRUCTION			
2 WATER WELL OWNER: NIES CONSTRUCTION RR#,ST. ADDRESS,BOX #: 10333 E. 21st N. STE #303		Board of Ag	riculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE: 6	7206 Application Nu	mher:
		ELEVATION:	mber.
WITH AN "X" IN SECTION BOX:	- n. ft.		4
N Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 48		ft.	ft.
Don't delay Malland		URFACE MEASURED ON mo	
''' ''-			s of pumping @ gpm s of pumping @ gpm
Est. Yield: gpm Well wat Bore Hole Diameter 12 in.	to 92 ft		to ft.
₩ELL WATER TO BE USED AS:		9 Dewater	
1. Domestic 3. Feedlot 5. Public wa	ter supply 🤙 Lawn	and garden only	12. Other (Specify below)
	ater supply 8. Air co	16	
S Was a chemical/bacteriological sample submitted to D submitted		NO ; If yes, Water Well Disinfected?	what mo/day/yr was sample YES NO
5 TYPE OF CASING USED: 5 Wrought Iron 7 Fiberglass			\geq
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	9. Other (Specify	y below) CASING JOINTS:	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete ti	le SDR-26		Weided Clamped
Blank casing diameter 5 in. to 50 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	ige No214
TYPE OF SCREEN OR PERFORATION MATERIAL:		, , and another of gas	.214
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Ce	ment 12. None used (oper	n hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
	92 ft.	_	
	,	From ft.	to ft.
From ft. to GRAVEL PACK INTERVALS: From 24 ft. to	00	From ft.	to ft.
TION 2	7- 11.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other ben	tonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From	ft. to	ft., From	ft. to ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
	11. Fuel storage	14. Abandon water well	16. Other (specify below)
O Food word 40 Food Wasse steemen			
3. Watertight sewer line 6. Seepage pit 9. Feed yard Direction from well? West		How many feet? 10	ft. plus
From To LITHOLOGIC LOG	From To		OGIC LOG
0 3 topsoil			
3 8 clay			
8 30 brown shale			
30 86 gray shale			
86 92 limestone	 		
	 	<u> </u>	
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and			
was completed on (mo/day/year) 1/31/17 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/3/17			
under the business name of Harp Well and Pump Service	by (signature)	ToddS	S. Harp