WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER FRACTION TOWNSHIP NUMBER RANGE NUMBER NW 1/4 Sedgwick NE SE 1/4 24 Т 27 S R 2E E/W Distance and direction from nearest town or city street address of well if located within city? 15601 E. Morningside St. Wichita, Kansas WATER WELL OWNER: SUPERIOR HOMES Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1109 S. Rock Road CITY, STATE: Wichita, Kansas ZIP CODE Application Number: 100 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: **FLEVATION:** WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered: ft. ft. Ν WELL'S STATIC WATER LEVEL 18 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Well water was Pump test data: ft. after hours of pumping @ gpm NW. ΝE Est. Yield: apm Well water was ft. after hours of pumping @ gpm Ĩ Bore Hole Diameter 12 to 100 and ft. in. WELL WATER TO BE USED AS: 11. injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE-3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted (YES) Was Water Well Disinfected? NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4 ABS Blank casing diameter 5 40 Dia. in. to ft., ft.. Dia. ft. to in to 12 Casing height above land surface: 2.35 in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2. Brass 6. Concrete Tile 8. RMP (SR) 4. Galvanized 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 40 100 From to ft., From ft. to ft. From to ft., From ft to ft. **GRAVEL PACK INTERVALS:** 24 ft. to 100 From ft., From ft. to ft. From ft. to ft. From ft. ft. **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 24 ft. From ft. ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Yet 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit Direction from well? How many feet? From To LITHOLOGIC LOG From Τо LITHOLOGIC LOG topsoil 14 clay 14 brown shale 100 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed under my jurisdiction and or 3. was completed on (mo/day/year) 3/24/17 and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 3/27/17 Kansas Water Well Contractor's License No. 236 Todd S. Harb by (signature) under the business name of Harp Well and Pump Service