Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER FRACTION TOWNSHIP NUMBER RANGE NUMBER swSedgwick 1/4 SE 1/4 NE 1/4 11 Т 27 S R 2E E/W Distance and direction from nearest town or city street address of well if located within city? 13914 E. Steeple Chase Ct. Wichita, Kansas WATER WELL OWNER: RITCHIE BUILDING CO. Board of Agriculture, Division of Water Resource 8100 E. 22nd Bldg. 1000 RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: 90 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. N 38 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/daylyr: 5/26/17 Pump test data: Well water was hours of pumping @ NEft. after gpm NW Est. Yield: gpm Well water was ft. after hours of pumping @ ⋚ 12 Bore Hote Diameter to 90 ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) YES submitted Was Water Well Disinfected? NΩ TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter to 50 ft. Dia. ft., Dia. in. in. to in. ft. to 12 in., Weight: 2.35 Wall thickness or gauge No. Casing height above land surface: lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 11. Other (specify) N/A 7. PVC 9 ABS 1. Steel Stainless Steel 5. Fiberglass 2 Brass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 4 Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill stot Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched Wire wrapped 8. Saw cut 10. Other (specify) N/A 90 SCREEN - PERFORATION INTERVAL 50 From fŁ, From H to ft. From fŁ to ft., From Ħ fl. to 24 ft 90 GRAVEL PACK INTERVALS: to From ft.. From to ft. From ft. to ft.. From ft ft **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 24 ft., From ft. to ft.. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line Direction from well? East How many feet? 10 ft. plus LITHOLOGIC LOG LITHOLOGIC LOG From Τo From Τo <u>topsoil</u> 3 R clay 20 8 brown shale 20 85 gray shale 85. 90 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my judsdiction and 5/26/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/30/17 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb