WATER WELL RECORD KSA 82a-1212 Form WWC-5 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW Sedgwick SE 1/4 NE 1/4 1/4 35 Т 27 S 2E R Ε/W Distance and direction from nearest town or city street address of well if located within city? 13510 Mustang Circle Wichita, Kansas WATER WELL OWNER: BUCKERT, AARON CONTRACTING INC. Board of Agriculture, Division of Water Resource P.O. Box 780405 RR#,ST. ADDRESS BOX #: Wichita, Kansas CITY, STATE ZIP CODE: Application Number: 105 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. ELEVATION: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. 28 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/vr. 5/25/17 Pump test data: Well water was NE ft. after hours of pumping @ QDIT: Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ⋽ 12 Bore Hole Diameter to 105 and in. ft. WELL WATER TO BE USED AS: 11. Injection well Dewatering 5. Public water supply 7. Lawn and garden only SW SE-3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? submitted (YES) Was Water Well Disinfected? TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: C Glued Threaded Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 2. PVC 8. Concrete tile 4. ABS Blank casing diameter 5 40 in. Dia. ft.. Dia. in. to in. ft to 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL; 7. PVC 11. Other (specify) N/A 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) N/A SCREEN - PERFORATION INTERVAL 40 ft. 105 From to ft., From ft. to ft. ft. to ft., From fł to ft. 24 GRAVEL PACK INTERVALS: ft. 105 From to ft.. From ft. to ft ft. From to ft.. From ft. fŁ **GROUT MATERIALS:** Other Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: 24 From ft to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage tagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit North How many feet? 10 ft. plus Direction from well? From To LITHOLOGIC LOG LITHOLOGIC LOG From Τo topsoil 20 clay 20 brown shale 35 105 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 5/25/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/30/17 under the business name of Harp Well and Pump Service Todd S. Harb by (signature)