WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SE Sedgwick 1/4 NE SE 1/4 24 т 27 S R 2E E/W Distance and direction from nearest town or city street address of well if located within city? 15708 E. Morningside Wichita, Kansas WATER WELL OWNER: SUPERIOR HOMES Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1109 S. Rock Road Wichita, Kansas ZIP CODE: 67207 CITY, STATE: Application Number: 90 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ELEVATION: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr. Pump test data: Well water was NEft. after hours of pumping @ NW gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ⋽ 12 Bore Hole Diameter ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SE 5. Public water supply 7. Lawn and garden only SW 1. Domestic 3. Feedlot 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) s YES submitted Was Water Well Disinfected? NO TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: CGlued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) Steel Welded Clamped SDR-26 Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter 40 ft. Dia. ft. Dia. in. to in. ft. to 12 2.35 Casing height above land surface: in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 8. RMP (SR) 6. Concrete Tile 12. None used (open hole) 2 Brass 4. Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 90 40 ft From to ft. From to ft. ft. From to ft.. From to ft 24 GRAVEL PACK INTERVALS: ft. 90 From to ft., From to ft. ft. From to ſt., From ft. ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From ft. 24 ft., From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. West 9. Feed yard 12. Fertilizer storage 6. Seepage pit How many feet? 15 ft. plus Direction from well? <u>From</u> LITHOLOGIC LOG LITHOLOGIC LOG Τо From Tο topsoil 10 clay 10 35 brown shale 35 85 grey shale 85 90 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 7/5/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/7/17 Todd S. Harp under the business name of Harp Well and Pump Service by (signature)