		WATER W	ELL REC	ORD I	Form W\	NC-5 K	(SA 82a-	1212			
1 LOCATION OF WAT								NSHIP NUMBER		RANGE NUMBER	
Sedgwick	om nearest town or city	SW 1/4		/4 NE	1/4	3	<u> </u>	27 s		R 2E	EW
12418 E. 27	•		Vichita,Ka	•							
2 WATER WELL		KERT, AAR			NG INC.						
RR#,ST. ADDRES		Box 780405						Board o	of Agriculture, Di	vision of Wa	ter Resource
CITY		hita,Kansas				IP CODE: 6	57278	Applicatio	n Number:		
3 LOCATE WELL'S	OCATION 4 [DEPTH OF COMP	PLETED WEL	.L: 10)0 ft.		ELEVATIO	N:			
N N	Dep	oth of groundwate			f			ft.			ft.
	- X	ELL'S STATIC W				OW LAND S		ASURED ON		7/6/1	
NW -	-NE -	Est. Yield:	ımp test data: gpm	Well wa Well wa			ft. after ft. after		hours of pump hours of pump		gpm gpm
M ≧ije	E B	ore Hole Diamete	- 44	in.		100 ft			in.	to	ft.
- -	1 1	ELL WATER TO E						9. Dew	atering	11. Injecti	on well
sw			. Feedlot				and garden		12. (itoring well	Other (Spe	cify below)
		las a chemical/bacte		6. Oil field vile submitted to		YES	NO		yes, what mo	/day/yr wa	s sample
	sut	bmitted			•		Water Well D		YES	NC	<u> </u>
5 TYPE OF CA	SING USED: 3. RPM (SR	5. Wrought	t Iron	7. Fiberglass	9. C	ther (Specif	y below) (CASING JOIN			Threaded
2. PVC	> 4. ABS	6. Asbesto	s-Cement	8. Concrete t	_{ile} SD	R-26			Welded	1 (Clamped
Blank casing diame	_	in. to	50 ft.,	Dia.	in.	to	ft.,	Dia.	in.	to	fL
Casing height above	e land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wa	II thickness or	gauge No.	.214	
I	OR PERFORATION	-							30030	.217	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)											
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous sid			Gauzed wrap	•		orch cut		Orilled holes		None (op	en hole)
2. Louvered shut	ter 4. Key pu	inched 6,	Wire wrappe	d		w cut	10. 0	Other (specify	r)		
SCREEN - PERFOR	ATION INTERVAL	From	50 ft.	-		ft.,	From	ft.		to	ft.
		From	ft.			ft.,	From	ft,		to	乱
GRAVEL P	ACK INTERVALS:	From	24 ft.	_	200	ft.,	From	ft.		to	ft.
- 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2		From	ft.	te	<u> </u>	ft.,	From	ft.		to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout						3. Bentonite Other bentonite hole plug					
Grout intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:					ft.		ft.,	From	ft.	to	ft.
Septic tank 4. Lateral lines 7. Pit privy						0. Livestock pens 13. Ir			secticide storage 15. Oil well/Gas well		
2. Sewer lines	5. Cess P	8 loo	s. Sewage lag	joon	11. Fuel sto	rage	14. Ab	andon water i	well 16. C	Other (spec	cify below)
3. Watertight sew	***	ge pit 9	. Feed yard	,	12. Fertiliza	r storage			20.6		
From To		LITHOLOGIC	CLOG		From	То	Hov	many feet?	20 it. pius DLOGIC L		
0 3	topsoil	THOLOGI	0 200		1 10111	10-	 	LITTE	<u>JLOGIÇ L</u>	.00	
3 8	elây		,							_	
8 70	brown shale	and shale			 	 	-				
70 95 95 100	gray shale limestone					 				 ·_	
	-				 	<u> </u>	<u> </u>		-··- <u>-</u> ··		
	 				 	<u></u>	<u> </u>				
	_				_	ļ					
	-				 	 					
					<u> </u>					-	
7 Contractor's or	Landowner's Certific	ation: This water	well was 1.	constructed) 2. re	constructe	d or 3.	plugged	under my	jurisdiction	and
was completed or	(mo/day/year)	7/6/17	an	d this record	is true to the	e best of my	knowledge a	nd belief.			
Kansas Water We	II Contractor's Licens	e No. 236		This weter w	ell record wa	as completed	d on (mo/day/	year)	7/10/17		
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp											
	P					•		UUU	S. TI	MP	