WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER LOCATION OF WATER WELL: FRACTION **TOWNSHIP NUMBER** RANGE NUMBER swSedgwick SE 1/4 1/4 NE 1/4 11 T 27 S R 2E E/W Distance and direction from nearest town or city street address of well if located within city? 13802 Steeplechase Wichita, Kansas WATER WELL OWNER: NIES CONSTRUCTION Board of Agriculture, Division of Water Resource 10333 E. 21st N. #303 RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 85 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: ft. ft. Depth of groundwater Encountered: ft. 39 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/vr. 7/7/17 Well water was Pumo test data: ft. after hours of pumping @ NE qpm NW Est. Yield: Well water was ft after hours of pumping @ gpm ≌ Bore Hole Diameter 12 to 85 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only - SiW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (YES) submitted Was Water Well Disinfected? TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: CGlued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 40 Dia. ft.. Blank casing diameter in. to ft.. in. Dia. ft to in. to 12 2.35 Casing height above land surface: in., Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC > 3. Stainless Steel 5. Fiberalass 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 2. Brass Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 40 85 From to ft., From ft. to ft. ft. From to ft., From fi to ft. 24 **GRAVEL PACK INTERVALS:** ft. to 85 From ft., From ft. to ft From ft. to ft.. From ft. **GROUT MATERIALS:** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 24 ft.. From ft. to ft., From ft. What is the nearest source of possible contamination; 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard Watertight sewer line 6. Seepage pit How many feet? 10 ft. plus Direction from well? From Τo LITHOLOGIC LOG From To LITHOLOGIC LOG 3 topsoil n 2 <u>clay</u> <u> 30</u> brown shale <u> 30</u> <u>80</u> gray shale 80 85 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed 3. under my jurisdiction and 7/7/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 7/10/17 by (signature) Todd S. Harb under the business name of Harp Well and Pump Service