WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE NE 1/4 1/4 NE 1/4 T 27 S R 2E E/W Distance and direction from nearest town or city street address of well if located within city? 29th North and Woodridge Wichita, Kansas WATER WELL OWNER: RITCHIE DEVELOPMENT Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 8100 E. 22nd Bldg. 1000 Wichita, Kansas ZIP CODE: 67226 CITY, STATE: Application Number: 105 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ff WELL'S STATIC WATER LEVEL 44 FT. BELOW LAND SURFACE MEASURED ON mo/day/vr. 6/30/17 Pump test data: Well water was ·NW NE ft. after hours of pumping @ **OD**ITI Est. Yield: Φ gpm Well water was ft. after hours of pumping @ gpm ≣ 12 Bore Hote Diameter to 105 ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE-5. Public water supply 7. Lawn and garden only 1. Domestic 3. Feedlot 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; if yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? S submitted (YES) Was Water Well Disinfected? NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 2. PVC Asbestos-Cement 8. Concrete tile 4. ABS Blank casing diameter 5 45 to Dia. in. ft.. Dia. to in. to ft. 12 Casing height above land surface: Weight: 2.35 in., lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 9 ABS 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 105 From to ft.. From ft. to ft. ft. From to ft., From ft to ft. GRAVEL PACK INTERVALS: 24 ft. to 105 From ft., From ft. to ft From ft. to ft., From ft. to ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 24 ft From ft. to ft.. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit North How many feet? 20 ft. plus Direction from well? From Тο LITHOLOGIC LOG From То LITHOLOGIC LOG topsoil 12 clay 12 **70** brown shale 70 100 grey shale 100 105 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and plugged was completed on (mo/day/year) 6/30/17 and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 7/3/17under the business name of Harp Well and Pump Service Todd S. Harb by (signature)