	WATER WELL RECORD FO	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL:	FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick	NW 1/4 SE 1/4 NE	1/4 12	т 27 s	R 2E E/W
Distance and direction from nearest town	or city street address of well if located within city?			
15611 Rockhill Ct. Wichita, Kansas				
2 WATER WELL OWNER: I	RITCHIE DEVELOPMENT			
	8100 E. 22nd Bldg. 1000		Board of Agr	iculture, Division of Water Resource
	Wichita, Kansas	ZIP CODE:	Application Nut	nber:
3 LOCATE WELL'S LOCATION	4 DEPTH OF COMPLETED WELL: 123	<b>3</b> ft,	ELEVATION:	
WITH AN "X" IN SECTION BOX:		ft.	ft.	ft.
N N	Depth of groundwater Encountered:			
	WELL'S STATIC WATER LEVEL 32		IRFACE MEASURED ON mo/	
a	Pump test data: Well wate			s of pumping @ gpm
W HE	Est. Yield: gpm Well wate			s of pumping @ gpm
1 1 1	Bore Hole Diameter 12 in.	to <b>123</b> ft.	and in.	to ft.
	WELL WATER TO BE USED AS:	er supply 7. Lawn a	9. Dewater	•
				12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? VES NO ; If yes, what mo/day/yr was sample				
S	Was a chemical/bacteriological sample submitted to De submitted		Vater Well Disinfected?	YES NO
5 TYPE OF CASING USED:	oboli integ			$\sim$
	5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS:	Glued Threaded
		SDR-26		Welded Clamped
	55		<b>A</b> D:-	
Blank casing diameter	5 in. to 50 ft., Dia.	in. to	ft., Dia.	in, to ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OP	ENINGS ARE:			
	Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)
		8. Saw cut		
2. Louvered shutter 4. I	Key punched 6. Wire wrapped	O. Saw Cur	10. Other (specify)	
SCREEN - PERFORATION INTER	VAL From <b>50</b> ft. to	123 ft.,	From ft.	to ft.
	From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVA	NLS: From 24 ft. to	123 ft.,	From ft.	to ft.
	From ft. to	ft.,	_	
		ιι.,		to ft.
	Neat cement 2. Cement Grout	3. Bentonite	Other bent	tonite hole plug
Grout Intervals: From	4 ft. to 24 ft., From	ft. to	ft., From	ft. to ft.
What is the nearest source of possi	7 Dit meters 11	D. Livestock pens	13. Insecticide storage	15, Oil well/Gas well
·	ateral lines	1. Eucletorano	·	18 Other (encels helow)
2. Sever lines 5. Cess Fool				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
Direction from well? East			How many feet? 50	
From To	LITHOLOGIC LOG	From To	LITHOLO	DGIC LOG
0 3 topsoil				
3 8 clay			<u> </u>	
8 40 brown sh				ui) an an 1 - 1 - 1
40 120 grey shal				
120 123 limestone	e			
7 Contractor's or Landowner's	Certification: This water well was 1. constructed	) 2. reconstructed	or 3. plugged	under my jurisdiction and
7 Contractor's or Landowner's was completed on (mo/day/year		2. reconstructed s true to the best of my		under my junisdiction and
	r) 8/25/17 and this record is		knowledge and belief.	under my jurisdiction and
was completed on (mo/day/year Kansas Water Well Contractor's	r) 8/25/17 and this record is	s true to the best of my	knowledge and belief.	1/17