	WATER WEL	L RECORD	Form WV	VC-5 K	SA 82a-121	2		
1 LOCATION OF WATER WELL:	NYE					P NUMBER RANGE NUMBER 7 S R 2E E/W		
Sedgwick		.,	1/4	24	т 27	7 S	R 21	E/W
Distance and direction from nearest town or cit 15703 E. Morningside	-	ita, Kansas						
	PERIOR REALT				H 1			
	9 S. Rock Road					Board of Agric	culture, Division of V	later Resource
CITY, STATE: Wid	chita, Kansas		ZI	P CODE: 6	7207	Application Num	ber:	
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPLE	TED WELL:	90 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:	epth of groundwater Er	ncountered:	ft.			ft.	2 /1	1/18 ft.
1,	VELL'S STATIC WATE	R LEVEL 36	FT. BELC	W LAND SU	IRFACE MEASU	RED ON mo/d	ay/yr:	
NW - NE	Pump	test data: Well w	ater was		ft. after	hours	of pumping @	gpm
w E	Est. Yield:		vater was		ft. after	hours	of pumping @	gpm
1 1 1 1	Bore Hole Diameter	12 in.	to 9	90 ft.	and	in.	to	ft.
	VELL WATER TO BE U 1. Domestic 3. Fe		vater supply	7. Lawn a	nd garden only	> ^{9. Dewaterii}	٠,	ction well pecify below)
			water supply			10. Monitorin		becily below,
S	Was a chemical/bacteriolo			YES	NO		vhat mo/day/yr v	•
	submitted			Was V	Vater Well Disinf	ected? (=	<u> </u>
TYPE OF CASING USED: 1. Steel 3. RPM (5	5. Wrought Iro	n 7. Fiberglas	ss 9. O	ther (Specify	below) CAS	ING JOINTS: (Glued	Threaded
2. PVC 4. ABS	6. Asbestos-C	ement 8. Concrete	tile SD	R-26			Welded	Clamped
Blank casing diameter 5	in. to 40) ft., Dia.	in.	to	ft.,	Dia. i	n. to	ft.
, and the second	12 in	Weight:		bs. / ft.		ickness or gaug		
Casing height above land surface: TYPE OF SCREEN OR PERFORATION	,	weight.	2.55	DS. 7 II.	vvan ui	ickiless or gaug	je 140. "214	
1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. A	BS	11. Oth	ner (specify)		
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR) 10. A	sbestos-Cer	nent 12. No	ne used (open	hole)	
SCREEN OR PERFORATION OPENIA	NGS ARE:							
1. Continuous slot 3. Mill :	slot 5. Gai	ızed wrapped	7. T o	rch cut	9. Drill	ed holes	11. None (c	pen hole)
2. Louvered shutter 4. Key	punched 6. Wir	e wrapped	(8. Sa	w cut	10. Othe	er (specify)		
SCREEN - PERFORATION INTERVAL	- From	40 ft.	to 90	ft.,	From	ft.	to	ft.
SOREEN - FERT STOTIST IN TEREVISE	From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24 ft.	to 90	ft.,	From	ft.	to	ft.
0.000	From	ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1 Nea				•			onite hole pl	
<u> </u>	at cement 4 ft. to	 Cement Grout ft., From 		3. Bentonite		From	ft. to	ug ft.
What is the nearest source of possible	contamination:	,			ft.,			
1. Septic tank 4. Lateral lines 7. Pit privy 10. Li				vestock pens 13. Insecticide storage 15. Oil well/Gas well				
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below							ecity below)	
	page pit 9. Fe	eed yard	12. Fertilize	r storage		40.4		
Direction from well? South	LITUOL COLO		T =	I	How ma	any feet? 10 f		
From To	LITHOLOGIC I	_0G	From	То		LITHOLC	GIC LOG	
0 3 topsoil 3 10 clay	····			<u> </u>				
10 30 brown shale	е							
30 86 gray shale								
86 90 limestone			_					
			-	 				
				†				
				 				
		****			· · · · · · · · · · · · · · · · · · ·			
				 				
7 Contractor's or Landowner's Cert	tification: This water we	ell was 1. construct	ed) 2, re	constructed	d or 3,	plugged	under my jurisdic	tion and
was completed on (mo/day/year)	2/1/18				knowledge and I		, .	
Kansas Water Well Contractor's Lice				•	on (mo/day/yea		5/18	
				-	, , ,		-	
under the business name of Har	p Well and Pump	Service	Dy (s	ignature)	$T\epsilon$	oaa S	. Harp)