	WELL E			WWC-5			sion of Water	i		.	
	l Record			ge in Well Use			urces App. No		Well ID		
		ATER WEL	L:	Fraction	1/1/	1	tion Number	1		ge Number	
	y: SEDGW			SW¼ NW¼ SW	1/2 NW 1/4 35 T 27 S R 2 ■ E □ W						
	OWNER: I PADDOC	ast Name: KAT127th,	LLC	First:	direction from nearest town or intersection): If at owner's address, check here:						
		JTH 103RD									
3 LOCATE WELL											
WITH "			IPLETED WELL:90 A.				5 Latitude:(decimal degrees)				
SECTION BOX.				Encountered: 1)			Longit	Longitude:			
N WELL'S STATIC W								Source for Latitude/Longitude:			
			below land surface, measured on (mo-day-yr). 7/30/				GPS (unit make/model:)				
NWNE □ above land surface				, measured on (mo-da	y-yr)			(WAAS enabled? ☐ Yes ☐ No)			
Pump test data: Well w							☐ Land Survey ☐ Topographic Map				
Well v				s pumping gpm vater was ft.			☐ Online Mapper:				
after				urs pumpinggpm							
	Estimated Y	Estimated Yield:30gpm				6 Elevation:ft. Ground Level TOC					
S Bore Hole Dia				iameter: 10.5 in to 90 ft and			Source:				
7 WELL WATER TO BE USED AS:											
1. Domestic: 5. Public Water Supply: well ID											
☐ House	☐ Household 6. ☐ Dewaterin			g: how many wells?			11. Test Hole: well ID				
				echarge: well ID			☐ Cased ☐ Uncased ☐ Geotechnical				
Livesto		g: well ID									
3. ☐ Feedlo	2. ☐ Irrigation 9. Environmental Remediatio 3. ☐ Feedlot ☐ Air Sparge ☐ So										
4. Industr			13. Other (specify):								
4. ☐ Industrial ☐ Recovery ☐ Injection 13. ☐ Other (specify):											
Water well disinfected? Yes No											
8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other											
Casing diameter											
Casing height above land surface 15 in. Weight lbs./ft. Wall thickness or gauge No. SDR-26											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)											
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:											
☐ Continuous Slot ■ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)											
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)											
SCREEN-PERFORATED INTERVALS: From .40 ft. to .90 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From .29 ft. to 90 ft., From ft. to ft., From ft. to ft.											
G	RAVEL PA	CK INTERVA	ALS: Fron	n29 ft. to9	U ft., F	rom	ft. to	ft., From	ft. to	ft.	
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other.											
Grout Intervals: From											
Septic Tank											
Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well											
■ Watertight Sewer Lines											
☐ Other (Specify) Direction from well? SOUTH EAST Distance from well? .69											
10 FROM	TO TO		ITHOLO	CIC LOC	FRC			LITHO. LOG (cont.) or		CINTEDVALS	
0		TOP SOIL	LAMOLU	GIC LOG	- FAC	141	10 1	41110. 1AO (COIL.) 0	LUGGIN	JIVIERVALO	
1		CLAY	······································		_	\dashv			t. w		
10		LIME STON	E								
17		GRAY SHAL									
69	78	GYP/ GRAY	SHALE I	MIX							
78	90	SHALE									
					Note	s:					
	WELL#4										
11 CONTRACTORIS OR LANDONATERIS GERTIEFOATTON, TIL											
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) .7/30/2018 and this record is true to the best of my knowledge and belief.											
Kansas Wa	ursurcuon a ter Well Co	ntractor's Lice	ense No.	884 This V	⊷×≀.∨ Vater We	. and t I Reco	ord was com	nleted on (mo-day-y	ear) .8/16/	2018	
under the b	usiness nam	e of WENIN	GER.DR	ILUNG.LLC		Sig	mature . was	pleted on (mo-day-y	,		
Mail	1 white copy al	ong with a fee of	\$5.00 for <u>ea</u>	ch constructed well to: K	ansas Depa	rtment o	of Health and E	invironment, Bureau of W	ater, GWTS S	Section,	
				66612-1367. Mail one				e for your records. Telepl			
visit us at htt	p.//www.kdhek	s.gov/waterwell/i	naex.html		KSA 8	2a-12	14		revised	7/10/2015	