	WATER W	ELL REC	CORD F	orm W	WC-5 K	(SA 82a-1	212			
1 LOCATION OF WATER WELL:	FRACTION				SECTION NUMBER		F		RANGE NUMBER R 2E E/W	
Sedgwick Sedgwick	NE 1/4		1/4 <b>SW</b>	1/4	26	T	<b>27</b> S	R 2	E E/W	
Distance and direction from nearest town or c	ity street address of we Wichita, Kan		nin city?							
1226 S. Gateway  2 WATER WELL OWNER: FA	HSHOLTZ C		CTION							
	D. Box 818	ONOTAL	CIIOI				Board of Ag	riculture, Division of	Water Resource	
	dover, Kansas				ZIP CODE: 6	7002	Application Nu	ımber:		
3 LOCATE WELL'S LOCATION 4	DEPTH OF COME	PLETED WEI	LL: 8	<b>6</b> f		ELEVATION	l:			
WITH AN "X" IN SECTION BOX:	ப Depth of groundwate	er Encountere	ed:		ft.		ft.		ft.	
· · · · · · · · · · · · · · · · · · ·	WELL'S STATIC W	ATER LEVEL	. 22	FT. BEL	OW LAND SI	URFACE MEA	SURED ON mo.	/day/yr: <b>10</b> /	4/18	
NW NE	Pu	ımp test data	: Well wa	ter was		ft. after	hour	rs of pumping @	gpm	
w W	Est. Yield:	gpm	Well wa		0.0	ft. after		rs of pumping @	gpm	
	Bore Hole Diamete WELL WATER TO E		in.	to	<b>86</b> ft	. and	in.	to	ft. ection well	
SW - SE		. Feedlot	5. Public wa	ater suppl	7. Lawn	and garden o	9. Dewater		Specify below)	
	2. Irrigation 4	Industrial	6. Oil field v				10. Monitor	ing well		
S	Was a chemical/bacte	eriological samp	ole submitted to	Department		NO	-	what mo/day/yr	was sample NO	
	submitted					Water Well Dis				
5 TYPE OF CASING USED: 1. Steel 3. RPM (	(SR) 5. Wrough	t Iron	7. Fiberglass		Other (Specify	y belo <b>w</b> ) C	ASING JOINTS:	Glued Welded	Threaded Clamped	
2. PVC 4. ABS	6. Asbesto	s-Cement	8. Concrete t	tile S	OR-26			Weided	Clamped	
Blank casing diameter 5	in. to	40 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height above land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall	thickness or gau	uge No214	4	
TYPE OF SCREEN OR PERFORATION	ON MATERIAL:	_						NI/A		
1. Steel 3. Stainless Steel		_	7. PVC		ABS		Other (specify)			
2. Brass 4. Galvanized	6. Concrete	lile	8. RMP (SR)	10.	Asbestos-Ce	ment 12.	None used (oper	n noie)		
SCREEN OR PERFORATION OPENI		<b>^</b>				0.5	ممام ط الممالية	44 None /	anan hala)	
1. Continuous slot 3. Mill	-	Gauzed wra			orch cut		rilled holes		open hole)	
2. Louvered shutter 4. Key	punched 6.	Wire wrappe	ed		Saw cut	10. 0	ther (specify) N	N/A		
SCREEN - PERFORATION INTERVAL	L From	<b>40</b> ft	t. to	86	ft.,	From	ft.	to	ft.	
	From	ft			ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From	<b>24</b> ft	t. to	o <b>86</b>	ft.,	From	ft.	to	ft.	
	From	ft	to	<u> </u>	ft.,	From	ft.	to	ft.	
	at cement	2. Cemei		<	3. Bentonite	$\triangleright$	Other			
Grout Intervals: From What is the nearest source of possible	4 ft. to	<b>24</b> ft.	, From	,	t. to	ft.,	From	ft. to	ft.	
1. Septic tank 4. Lateral lines 7. Pit privy				10. Livestock pens		13. Insecticide storage 15		15. Oil well	Gas well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well						16. Other (s	pecify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage										
Direction from well? East				_		How	many feet? 10			
From To	LITHOLOGI	C LOG		From	To_		LITHOL	OGIC LOG		
0 3 topsoil 3 8 clay										
8 28 brown shale	e									
28 86 gray shale										
				<del> </del>						
				+	<del> </del>					
				+						
						<u> </u>				
Contractor's or Landowner's Cert	tification: This water	well was 1.0	constructe	2.	reconstructe	d or 3.	plugged	under my jurisdi	ction and	
was completed on (mo/day/year)	10/4/18	a	nd this record	is true to t	he best of my	knowledge an	d belief.			
Kansas Water Well Contractor's Lice	ense No. 236		This water w	ell record	vas completed	d on (mo/day/y	rear) 10	/5/18		
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb										