		WATER V	VELL RI	ECORD	Form	wwc	-5 K	SA 82a-1	1212			
1 LOCATION OF WATER	WELL:	FRACTION	~				NUMBER		SHIP NUMBER	i	NGE NUN	
Sedgwick		SE 1/4		1/4 SE	1/4	1	13	T	27 S	R	2E	E/W
Distance and direction from r 544 N. Belle Te	-	reet address of w		within city? chita, Kan:	202							
2 WATER WELL OW		HOLTZ (343							
RR#,ST ADDRESS,B		30x 818							Board o	of Agriculture, Divis	ion of Wa	ter Resource
CITY, ST	TATE: Andor	ver, Kansas	s			ZIP C	ODE: 67	7002	Applicatio	n Number:		
3 LOCATE WELL'S LOCATE WITH AN "X" IN SECTI	ATION 4 DE	EPTH OF COM	IPLETED V	VELL:	90	ft.		ELEVATIO	N:			
WITH AN X IN SECTI		h of groundwat	ter Encount			ft.			ft.			ft.
	WEL	L'S STATIC W					LAND SU		ASURED ON .		10/19/	
1 1 1	NE	Est. Yield:	ump test da		water was water was			ft. after ft. after		hours of pumpin hours of pumpir		gpm g p m
w Wile	1 1	re Hole Diamet	gpm ter 1			to 90	ft.			in,	to	ft.
-	1 1	L WATER TO		AS:					9 Dew		1. Inject	ion well
sw	1 1		3. Feedlot					nd garden			her (Spe	cify below)
	`	Irrigation s a chemical/bac		al 6. Oil field			3. Air con YES	ditioning NO		itoring well yes, what mo/d	ay/yr wa	is sample
s		nitted	teriological sa	ample suomitteu	то Берант	EIRT		ater Well D		YES	NO	
5 TYPE OF CASIN		5. Wroug	ht Iron	7. Fibergla	ss	9. Other	r (Specify	below) (CASING JOIN	TS: Glued	1	Threaded
1. Steel	3. RPM (SR)	J	tos-Cement	Ū		SDR-2	26			Welded	1	Clamped
2. PVC Blank casing diameter	4. ABS 5 ir	n. to	45 ft			in.	to	ft.,	Dia.	in.	to	ft.
1	-	12 in.,	4 5 K	•	2.35						.214	π.
Casing height above la		,		Weight:	2.33	lbs. /	/ π.	vva	III thickness or	gauge No.	.214	
	Stainless Steel	5. Fiberglas	ss (7. PVC		9. ABS		11	. Other (specif	_{fy)} N/A		
2. Brass 4. 0	Galvanized	6. Concrete	Tile	8. RMP (SF	₹)	10. Asbe	estos-Cen	nent 12	. None used (open hole)		
SCREEN OR PERFOR	ATION OPENINGS	ARE:										
1. Continuous slot	3. Mill slot	: 5	. Gauzed w	rapped	_	7. Torch	cut		Orilled holes		one (op	en hole)
2. Louvered shutter	4. Key pur	nched 6	. Wire wra	pped		8. Saw c	ut	10. 0	Other (specify	y) N/A		
SCREEN - PERFORATI	ION INTERVAL	From	45	ft.	to 9	90 ft.	٠,	From	ft.		to	ft.
		From		ft.	to	ft.		From	ft.		to	ft.
GRAVEL PACE	(INTERVALS:	From	24	ft.	to	90 ft.	.,	From	ft.		to	ft.
		From		ft.	to	ft	.,	From	ft.		to	ft.
6 GROUT MATERIAL	LS: 1. Neat ce	∍ment	2. Cer	ment Grout		3. B	entonite	>	Other			
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:							to	ft.,	From	ft.	to	ft.
1. Septic tank 4. Lateral lines 7. Pit privy					10. Liv e	10. Livestock pens			13. Insecticide storage 15. Oil well/Gas well			s well
2. Sewer lines	5. Cess Po	oi	8. Sewage	lagoon	11. Fue	el storag	е	14. Ab a	andon water	well 16. Ot	her (spe	cify below)
3 Watertight sewer I		e pit	9. Feed ya	rd	12. Fer	tilizer ste	orage					
Direction from well?	East		10 1 00	,.				Hov		50 ft. plus		
From To	opsoil	ITHOLOG	IC LOG		Fre	om	То		LITH	DLOGIC LC)G	
	lav	, , , , , , , , , , , , , , , , , , ,										
	rown shale											
40 90 8	ray sand											
		***		***************************************			<u> </u>					
					_							
7 Contractor's or La	ndowner's Certifica	ation: This wat	er well was	1. construc	ted) 2	recon	structed	or 3,	plugged	under my j	urisdictio	n and
was completed on (m		10/19/18		and this reco		•				,		
	• • •		-				-	on (mo/day		10/22/18		
Kansas Water Well C												
under the business na	ame or Harp V	ven and Pu	ımp Serv	vice		by (signa	itule)		<u>i oaa</u>	<u>/S. Ho</u>	<u>wp</u>	