WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick 27 SE 1/4 11 Т R **2E** E/W 1/4 Distance and direction from nearest town or city street address of well if located within city? 13805 E. Steeple Chase Circle Wichita, Kansas **NIES CONSTRUCTION** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10333 E 21st N. #303 Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: 4 DEPTH OF COMPLETED WELL: 80 **ELEVATION:** ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft ft 35 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 12/13/18 Pump test data: Well water was ft. after hours of pumping @ NM NE gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm 12 to 80 Ξ Bore Hole Diameter in. and in. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 8. Air conditioning 10. Monitoring well 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES) NO TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Clamped Welded SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter to 30 ft.. Dia to ft.. Dia to ft. Casing height above land surface: 12 Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9 ABS 11. Other (specify) 1 Steel 8. RMP (SR) 12. None used (open hole) 2 Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 30 ft. 80 ft.. From From to ft. From ft. to ft., From ft. ft. **GRAVEL PACK INTERVALS:** 24 to 80 From ft.. From ft to ft. From ft. to ft.. From fŧ **GROUT MATERIALS:** Other 2. Cement Grout bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: 24 From ft.. From to ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit West How many feet? 10 ft. plus Direction from well? From LITHOLOGIC LOG LITHOLOGIC LOG To From Tο topsoil clav 12 51 brown shale 51 80 grey shale

Contractor's or Landowner's Certification: This water well was 1. **constructed** 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) 12/13/18 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/17/18

under the business name of Harp Well and Pump Service

by (signature)

<u>Todd S. Harp</u>