	V	VATER WE	LL RECORD	Forr	n WW	C-5 K	SA 82a-121	2		
1 LOCATION OF WATER V	WELL: F	RACTION			SECTION	ON NUMBER			RANGE NU	
Sedgwick		NW 1/4	SE 1/4 I	NE 1/	4	11	T 2	7 <u>s</u>	R 2E	E/W
Distance and direction from n	earest town or city stree	et address of well i	f located within city?		-					
14002 E. Rock I			ichita, Kansas							
2 WATER WELL OW	NER: FAHSH	IOLTZ CO	NSTRUCTIO	N				Deard of A	outure Divisifill	ater Basourse
RR#,ST. ADDRESS,BO	OX #: P.O. Bo	ox 818						Board of Agri	culture, Division of W	aler Resource
CITY, ST	ATE: Andove	er, Kansas			ZIP	CODE: 6	7002	Application Nun	nber:	
3 LOCATE WELL'S LOCA	ATION 4 DEF	PTH OF COMPL	ETED WELL:	86	ft.		ELEVATION:			
WITH AN "X" IN SECTION	ON BOX:	of groundwater I			ft.			ft.		ft.
N N	·	'S STATIC WAT		8			JRFACE MEASU		lav/vr: 1/16	
						LAND ST	ft. after		s of pumping @	gpm
NW	× I	st. Yield:		ell water w ell water w			ft. after		s of pumping @	gpm
M M		Hole Diameter	gpm W 12 in.		to 86	ó ft		in.	to	ft.
~ .		WATER TO BE			0 00	,	210		44 Inter	ction well
			Feedlot 5. Publ	ic water s	supply <	7. Lawn	and garden only	Solution ⇒ 9. Dewateri	12. Other (Sp	
	2. In	rigation 4.1					nditioning	10. Monitori		····, -···,
Ls		•	ological sample submit			YES	NO	; If yes,	what mo/day/yr w	-
	submi	itted		-			Water Well Disin	fected?	YES N	10
5 TYPE OF CASIN	IG USED:	5. Wrought I	ron 7. Fiber	alass	9. Oth	er (Specif	y below) CAS	SING JOINTS:	Glued	Threaded
1. Steel	3. RPM (SR)	-		-	SDR	_26			Welded	Clamped
2. PVC	4. ABS	6. Asbestos-	-Cement 8. Conc	rete tile	301	20				
Blank casing diameter	5 in.	to 4	40 ft., Dia	а.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
	Stainless Steel	5. Fiberglass	7. PVC	>	9. AB	S	11. Of	her (specify)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slot	3. Mill slot		auzed wranned		7 Тог	ch cut	9 Dril	led holes	11. None (c	pen hole)
					\frown					
2. Louvered shutter	4. Key pund	ched 6.W	Vire wrapped	(8. Sav	vcut	10. Oth	er (specify)		
SCREEN - PERFORATI	ION INTERVAL	From	40 ft.	to	86	ft.,	From	ft.	to	ft.
		From	ft,	to		ft.,	From	ft.	to	ft.
GRAVEL PACK		From	24 ft.	to	86	ft.,	From	ft.	to	ft.
GIVAVEL PACE	A INTERVALO.				00				10	
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIAL	LS: 1. Neat cer	ment	2. Cement Grout	t	3.	Bentonite	e	Other bent	tonite hole plu	ug
Grout Intervals:	From 4	ft. to	24 ft., F	rom	ft.	to	ft.,	From	ft. to	ft.
What is the nearest sour		7	Pit privy	10. L	Livestock	pens	13 Insect	icide storage	15. Oil well/0	Gas well
1. Septic tank	4. Lateral lin					•		•	16. Other (sp	
2. Sewer lines	5. Cess Poo		Sewage lagoon		Fuel stor	-	14. Aband	Ion water well	i si suisi (ap	
3. Watertight sewer		pit 9.	Feed yard	12.	Fertilizer	storage			<i>c</i> , 1	
Direction from well?	West						How m	any feet? 20		
From To	Lľ	THOLOGIC	LOG		From	То		LITHOLO	DGIC LOG	
	opsoil									
	lay								·	
	prown shale						<u> </u>			
	gray shale									
82 86 1	imestone	·····								
+		······								
		·								
7 Contractor's or La	andowner's Certificat	tion: This water	well was 1 conet	ructed	2 100	constructe	ed or 3,	plugged	under my jurisdic	tion and
P		water		alley	2. 180					
		1/16/10	1.4.7			hart of a	(knowlade	holiof		
was completed on (n	no/day/year)	1/16/19				-	y knowledge and			
was completed on (n Kansas Water Well C						-	y knowledge and ed on (mo/day/ye		17/19	
	Contractor's License	No. 236	This w		ecord wa	-	ed on (mo/day/ye	ar) 1/	17/19 5. Hart	,