	WATER WE	LL RECORD	Form WV	VC-5 K	SA 82a-121	2			
1 LOCATION OF WATER WELL:	FRACTION	1			R TOWNSHIP		RANGE NUMBER		
Sedgwick	NE 1/4	NW 1/4 SE	1/4	9	T 27	S	R 2E	E/W	
Distance and direction from nearest town or city:		located within city? Wichita, Kans	0.0						
2 WATER WELL OWNER: NIES	CONSTRUC		45						
	Board of Agriculture, Division of Water Resource								
•	nita, Kansas		Z	P CODE:		Application Num	nber:		
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPLI	ETED WELL:	76 ft.		ELEVATION:				
WITH AN "X" IN SECTION BOX:	oth of groundwater E		ft			ft.		ft.	
	ELL'S STATIC WAT	ER LEVEL 40	FT. BELC	W LAND SU	JRFACE MEASU	RED ON mo/o	lay/yr: 5/17	/19	
NWNE	Pum	p test data: Well v	vater was		ft. after	hours	of pumping @	gpm	
₩ W E Bo	Est. Yield:	3,	water was		ft. after	hours	of pumping @	gpm	
	ore Hole Diameter	12 in.	to ´	76 ft.	and	in.	to	ft.	
	ELL WATER TO BE . Domestic 3. F	: USED AS: feedlot 5. Public v	vater supply	7. Lawn	and garden only	9. Dewateri >	ng 11. injed 12. Other (Sp	tion well	
			water supply		nditioning	10. Monitorir		ecily below,	
_		ological sample submitted		YES	NO		what mo/day/yr w	•	
	bmitted			Was \	Vater Well Disinfo	ected?	$\overline{}$	10	
5 TYPE OF CASING USED: 1. Steel 3. RPM (SF	5. Wrought Ir	ron 7. Fibergla	ss 9. C	ther (Specify	below) CAS	ING JOINTS: (Glued	Threaded	
2. PVC 4. ABS	6. Asbestos-	Cement 8. Concrete	_{e tile} SD	R-26			Welded	Clamped	
	in. to 4	0 ft., Dia.	in.	to	ft., I	Dia.	in, to	ft.	
Casing height above land surface:	12 in.,	Weight:		bs. / ft.		ckness or galic	ge No214		
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENING	SS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)								pen hole)	
2. Louvered shutter 4. Key pu	unched 6. W	ire wrapped	8. Sa	w cut	10. Othe	r (specify)			
SCREEN - PERFORATION INTERVAL	From	40 ft.	to 76	ft.,	From	ft.	to	ft.	
	From	ft.	to	ft.,	From	ft.	to	ft,	
GRAVEL PACK INTERVALS:	From	24 ft.	to 76	ft.,	From	ft.	to	ft.	
	From	ft.	to	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1 Next				•					
2. Centent Grout 3. Bentonte Both of Pug								r g ft.	
What is the nearest source of possible contamination:									
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/G									
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								ecity below)	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? West	LITUOLOGIO	1.00	T F	T ==	How ma	ny feet? 12 f			
	LITHOLOGIC	LUG	From	То		LITHOLC	GIC LOG		
0 3 topsoil 3 39 brown shale									
39 74 grey shale									
74 76 limestone				ļ					
			1			,			
				<u> </u>					
			-	 					

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 5/17/19 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/20/19									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									