	WATER W	ELL REC	ORD F	orm WV	VC-5 K	(SA 82a-1	212			
1 LOCATION OF WATER WELL:	FRACTION			SEC	TION NUMBE	R TOWNS			RANGE NUMBER	
Sedgwick	SE 1/4	NW 1/		1/4	12	T	27 s	R 21	E E/W	
Distance and direction from nearest town or city s	treet address of well Wichita, Ka		n city?							
1703 N. Terhune 2 WATER WELL OWNER: SHAP	RP HOMES	11545								
Z	N. Collective	Ste. #A					Board of Agr	iculture, Division of V	Vater Resource	
CITY, STATE: Wich	ita, Kansas			z	IP CODE: 6	7206	Application Nur	mber:		
3 LOCATE WELL'S LOCATION 4 D	EPTH OF COMP	LETED WEL	L: 12	0 ft.		ELEVATION	l:			
WITH AN "X" IN SECTION BOX: Dep	th of groundwater	Encountered	l:	ft			ft.		ft.	
WE	LL'S STATIC WA	TER LEVEL	48	FT. BELC	W LAND S	URFACE MEA	SURED ON mo/	day/yr: 5/10	5/19	
NWNE		mp test data:	Well wat			ft. after		s of pumping @	gpm	
₩ E Bo	Est. Yield:	gpm 12	Well wa	ter was to	120 4	ft. after		s of pumping @	gpm ft.	
	re Hole Diameter LL WATER TO B		in.	το .	120 ft	and	in.	to 11 Inje	ction well	
1 X X I''-		Feedlot	5. Public wa	ter supply	7. Lawn	and garden o	9. Dewater	iiig '	pecify below)	
	Irrigation 4.	Industrial	6. Oil field w	ater supply	8. Air co	nditioning	10. Monitori	ng well		
•	as a chemical/bacter imitted	riological sample	e submitted to [Department?	YES	NO Water Well Dis		what mo/day/yr v	was sampie NO	
5 TYPE OF CASING USED:	milled							Glued	Threaded	
1. Steel 3. RPM (SR	5. Wrought	Iron	7. Fiberglass		ther (Specif	y below) C	ASING JOINTS:	Welded	Clamped	
2. PVC 4. ABS	6. Asbestos	s-Cement	8. Concrete ti	ile SD	R-26					
Blank casing diameter 5 i	in. to	50 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height above land surface:	12 in.,		Weight:	2.35	bs. / ft.	Wall	thickness or gau	ge No214		
TYPE OF SCREEN OR PERFORATION			71/0			44	Other (**)			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4. Galvanized	6. Concrete T	iie 8	. RMP (SR)	10. A	Asbestos-Ce	ment 12.	None used (open	riole)		
SCREEN OR PERFORATION OPENING		°		7 7-		0 D	rilled holes	11. None (onen hole)	
1. Continuous slot 3. Mill slo		Gauzed wrap	•		orch cut			TI. NONE (open noie,	
2. Louvered shutter 4. Key pu	nched 6. V	Nire wrapped	d		w cut	10. C	ther (specify)			
SCREEN - PERFORATION INTERVAL	From	50 ft.	to	120	ft.,	From	ft.	to	ft.	
	From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From	24 ft.	to	120	ft.,	From	ft.	to	ft.	
	From	ft.	to)	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat c		2. Cemen	t Grout		3. Bentonite	•	Other bent	tonite hole pl	ug	
Grout Intervals: From 4 What is the nearest source of possible cor	ft. to	24 ft.,	From	ft.	to	ft.,	From	ft. to	ft.	
1. Septic tank 4. Lateral	7	. Pit privy	1	0. Livesto	ck pens	13. inse	cticide storage	15. Oil well/	Gas well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify							ecify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage										
Direction from well? South						How	many feet? 10			
	ITHOLOGIC	CLOG		From	То		LITHOLO	OGIC LOG		
0 3 topsoil				<u> </u>	+					
3 11 clay 11 53 brown shale										
53 120 grey shale					1.					
				1						
				1						
				 	 	 				
				-	1					
					1			· ·		
7 Contractor's or Landowner's Certific	ation: This water	well was 1.C	constructed) 2. re	constructe	d or 3.	plugged	under my jurisdic	tion and	
was completed on (mo/day/year)	5/16/19		d this record		e best of my	knowledge ar	nd belief.			
Kansas Water Well Contractor's Licens	se No. 236				-	d on (mo/day/)		17/19		
under the business name of Harp					ignature)		Todd S			