			WATER	WELL R	ECORD	Forn	n WW	C-5 K	(SA 82a-1	212					
1 LOCATION OF WATER WELL:			FRACTION				SECT	ON NUMBE					RANGE NUMBER		
Sedgy				/4 SW		VE 1/4	<u> </u>	11	T	27 5	3	R	2E	E/W	
1		n nearest town or city s ple Chase Circ			within city? ta, Kansas										
	R WELL C		CONSTR			<u> </u>						4.7			
	ADDRESS		3 E. 21st N.		•					Boa	rd of Agric	culture, Divisio	n of Wat	er Resource	
	CITY,	STATE: Wich	ita, Kansa	S			ZIF	CODE: 6	7206	Applica	ation Num	ber:			
3 LOCATE	WELL'S LO	CATION 4	DEPTH OF CO	MPLETED \	WELL:	80	ft.		ELEVATION	N:					
WITH A	N "X" IN SEC N	Dep	oth of groundwa	ater Encoun	tered:		ft.			ft				ft.	
		WE	LL'S STATIC	WATER LE	VEL 30	FT.	BELOV	V LAND S	URFACE MEA	ASURED O	N mo/d	lay/yr:	6/1/1	9	
} I	MM	-NE		Pump test d		ll water w			ft. after			of pumping	_	gpm	
w Wile		$\times$ $\lfloor \cdot \rfloor_{a}$	Est. Yield:	gpm 1		ell water w	as to <b>8</b> 0	) <del>(</del> 1	ft. after		nours in.	of pumping	@ to	gpm ft.	
≥ w		,	ore Hole Diame				10 0		. and	0.0	"". ewaterii	44		on well	
1. +	-sw		Domestic	3. Feedlot	5. Publi	ic water s	upply <sup>4</sup>	7. Lawn	and garden o	only 9. Di	ewatern	שיי	-	cify below)	
		2.	. Irrigation	4. Industri	ial 6. Oii fie	eld water	supply	8. Air co	nditioning		onitorin	-		a aamala	
' -	s		/as a chemical/ba bmitted	acteriological s	sample submitte	ed to Depar	tment?	YES Was	NO Water Well Di	•	ir yes, v	vhat mo/day	//yr wa: NC	-	
5 TYF	PE OF CAS	ING USED:					0.04			CASING JO	UNTS: (	Glued		hreaded	
	. Steel	3. RPM (SR	5. Wrou ₹)	ght Iron	7. Fiberg	glass		ner (Specif	y below)	2431146 36	/IIV10. V	Welded		Clamped	
2	. PVC	> 4. ABS	6. Asbe	stos-Cemen	t 8. Concr	rete tile	SDF	(-26							
Blank cas	ing diamete	er 5	in. to	30 f	t., Dia	١.	in.	to	ft.,	Dia.	i	in. to	)	ft.	
Casing h	eight above	land surface:	12 in.	,	Weight	: <b>2.3</b>	5 lb	s. / ft.	Wa	ll thickness	or gaug	ge No.	214		
TYPE OF	SCREEN C	OR PERFORATION				_		_		<b>0</b> 11	<b>'</b> '				
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)															
2. Bras		. Galvanized	6. Concre	te l'ile	8. RMP (	5K)	10. As	sbestos-Ce	ement 12.	. None use	a (open	riole)			
		RATION OPENING		5 Causad			7 Ta	-ht	o r	Orilled hole		11 No	ne ( on	en hole)	
	nuous slot			5. Gauzed		,		ch cut				11.140	ю ( ор		
2. Louve	ered shutte	er 4. Key pu	unched	6. Wire wra	apped	(	8. Sav	v cut	10. 0	Other (spe	сіту)				
SCREEN -	PERFORA	TION INTERVAL	From	30	ft.	to	80	ft.,	From	f	t.	te	)	ft.	
			From		ft.	to		ft.,	From	f	t.	te	)	ft.	
G	RAVEL PA	CK INTERVALS:	From	24	ft.	to	80	ft.,	From	f	ft.	te	)	ft.	
			From		ft.	to		ft.,	From	f	ft.	te	<b></b>	ft.	
6 GROU	JT MATERI	ALS: 1. Neat	cement	2. <b>Ce</b>	ment Grout		3	. Bentonit	e	Other	bent	onite hol	•	-	
	Intervals:	From		to	ft., Fr	om	ft.	to	ft.,	, Fro	m 4	ft.	to 2	34 ft.	
		ource of possible co 4. Lateral		n: 7. <b>Pit privy</b>			ivestocl	c pens	13. Insecticide storage 15. Oil well/Gas well						
									andon wat	er well	16. Oth	er (spe	cify below)		
	rtight sewe	r line 6. Seepa	ge pit	9. Feed y	ard	12. <b>F</b>	ertilizer	storage							
	from well?	South							How many feet? 10 ft. plus						
From	То		LITHOLOG	SIC LOG	}	F	rom	То		LIT	HOLC	GIC LO	<u>G</u>		
0	3	topsoil	<del></del>						-						
11	52	clay brown shale													
52	80	grey shale													
									<del>                                     </del>						
	<b></b>					_			<del> </del>						
	<u> </u>		w												
						_									
7 Con	tractor's or	Landowner's Certifi	cation: This wa	ater well was	s 1. constr	ucted	2. re	constructe	ed or 3.	plugge	d	under my ju	risdictio	n and	
		(mo/day/year)	6/1/19						y knowledge a	and belief.					
1		l Contractor's Licen	se No. 236						ed on (mo/day		6/4	4/19			
1		name of Harp		Pumn Sei				gnature)			7.0	. Ha	vh		
					·					, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	vv U				