WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number
County: Sedgwick	1/4 NW 1/4 NW 1/4 SE 1/4	
Street/Rural Address of Well Location	; if unknown, distance & direction	Global Positioning System (GPS) information:
from nearest town or intersection: If a	t owner's address, check here .	Latitude: (in decimal degrees)
15212 E Sundance St		Longitude: (in decimal degrees)
Wichita, KS 67230		Elevation:
		<u>Datum</u> :
Tanor	oltz Contruction	Collection Method:  GPS unit (Make/Model:)
0' 0' 7TD 0 1	Shannon Way Ct	☐ Digital Map/Photo, ☐ Topographic Map. ☐ Land Survey
City, State, 211 Code . Wichit	a, KS 67206	Est. Accuracy: $\square < 3 \text{ m}$ , $\square 3-5 \text{ m}$ , $\square 5-15 \text{ m}$ , $\square > 15 \text{ m}$
3 LOCATE WELL		
WITH AN "X" IN 4 DEPTH OI	F COMPLETED WELL 111	ft.
SECTION BOX: Depth(s) Grou	ndwater Encountered (1)88	ft. (2) ft. (3) ft.
N WELL'S STA	TIC WATER LEVELfi	below land surface measured on mo/day/yr
Pun	np test data: Well water was	ft. after hours pumping gpm
EST. YIELD.	gpm. Well water was	ft. after hours pumping gpm
w         E   Bore Hole Dia		ft., andft.
1 1 1 1 1 1 1	R TO BE USED AS: 🔲 Public wa	
Domestic		er supply   Dewatering   Other (Specify below)
☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well		
	o/day/yr sample was submitted	
Water well dis	infected?  Yes  No	
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter .5" in to		
Casing height above land surface 12" in., Weight 160 lbs./ft., Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
Steel Stainless Steel PVC Other (Specify)		
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)		
SCREEN-PERFORATED INTERVALS: From 71 ft. to 1.11 ft., From ft. to ft.		
Fromft. toft., Fromft. toft.		
GRAVEL PACK INTERVALS: From 20' ft. to 111 ft., From ft. to ft.		
From ft. to ft., From ft. to ft.		
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other		
Grout Intervals: From .3' ft.	to ft., From	ft. to ft., From ft. toft.
What is the nearest source of possible con	ntamination:	
	lines Pit privy Livestock	
Sewer lines Cesspoo		
1 D 11 Most		torage    Oil well/gas well from well . 27'
<del></del>	Distance FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 3 dirt	rkow r	TO ETITIO. LOG (WIR.) OF T LOGOTIVO INTERVALS
3 17 red clay		
17   1ed clay   17   17   17   17   17   17   17   1		
57 111 shaley lime		
or iii shaley liftle		
	-	
7 CONTRACTORS OF LANDOWN	PIS CEPTIFICATION. This	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, r		
under my jurisdiction and was completed on (mo/day/year) .9/28/15		
under the business name of Reiserer W	רום אמנד Well Drilling	by (grantura) Larry Paigorer
under the business name of Reiserer Well Drilling by (signature) Jerry Reiserer.  INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies		
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.		
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at		
http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212		Check: White Copy, Blue Copy, Pink Copy