KSA 82a-1212 WATER WELL RECORD Form WWC-5 RANGE NUMBER 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER FRACTION 2E SW NW 34 Т 27 S R EW Sedgwick NE 1/4 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 1710 S. Stephanie Wichita, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource 10008 W. York RR#,ST. ADDRESS,BOX #: ZIP CODE: 67225 Application Number Wichita, Kansas CITY, STATE: 85 4 DEPTH OF COMPLETED WELL: **ELEVATION:** ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 11/19/20 25 WELL'S STATIC WATER LEVEL gpm Well water was ft. after hours of pumping @ Pump test data: N₩ NE hours of pumping @ gpm ft. after Est. Yield: gpm Well water was ft. Bore Hole Diameter 12 and in. Σ 11. Injection well WELL WATER TO BE USED AS: 9. Dewatering 5. Public water supply <7. Lawn and garden only 9W SF-3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 8. Air conditioning 6. Oil field water supply 2. irrigation 4. industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) NO submitted CASING JOINTS: Glued TYPE OF CASING USED: 5 Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter Dia. ft. 5 · 30 ft.. Dia in. to in. to in. to 2.35 Casing height above land surface: Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 3. Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement 2. Brass 4. Galvanized Concrete Tile SCREEN OR PERFORATION OPENINGS ARE: 11. None (open hole) 9. Drilled holes 7. Torch cut 3. Mill slot 1. Continuous slot 5. Gauzed wrapped 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 30 ft. to 85 ft. From ft. ft. Fmm to From ft. ft. to ft.. ft. From to 24 85 **GRAVEL PACK INTERVALS:** to ft.. From ft. to ft. From ff From From to ft.. ft. to ft. Other **GROUT MATERIALS:** 6 bentonite hole plug 2 Cement Grout 3 Bentonite 1. Nest cement **Grout Intervals:** From ft. 24 ft., From ft. to ft., From to ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 6. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. 3 12. Fertilizer storage 9. Feed yard 6. Seepage pit How many feet? 10 ft. plus LITHOLOGIC LOG LITHOLOGIC LOG From From Τо Tο topsoil 3 11 clav 11 52 brown shale 52 85 grev shale under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed plugged 11/19/2020 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 11/23/20 Kansas Water Well Contractor's License No. 236 by (signature) under the business name of Harp Well and Pump Service