KOLAR Document ID: 1565289

WATER WELL		WWC-5		ivision of Wate					
Original Record		ge in Well Use		esources App. N		Well ID			
1 LOCATION OF	WATER WELL:	Fraction		ection Numbe	1		ge Number		
County:		1/4 1/4 1/4		~			\Box E \Box W		
2 WELL OWNER	: Last Name:	First:		treet or Rural Address where well is located (if unknown, distance and					
Business: Address:			direction from	rom nearest town or intersection): If at owner's address, check here:					
Address:									
City:	State:	ZIP:							
3 LOCATE WELL	4 DEDTH OF COL	MPLETED WELL: .		ft 5 T a444	.d		/1 · 11 · \		
WITH "X" IN		Encountered: 1)			5 Latitude:				
SECTION BOX:	2) ft. 3) ft., or 4) \[\subseteq Distribution of the content				Datum: WGS 84 NAD 83 NAD 27				
N	WELL'S STATIC WATER LEVEL:				e for Latitude/Longitud		.AD 21		
	below land surface, measured on (mo-day-yr				PS (unit make/model: .)		
NW NE		e, measured on (mo-day-			(WAAS enabled? ☐ Yes ☐ No)				
	· C 1	Pump test data: Well water was			☐ Land Survey ☐ Topographic Map				
W		after hours pumping g Well water was ft.			☐ Online Mapper:				
SW SE		s pumping							
	Estimated Yield:		SP		6 Elevation :ft. ☐ Ground Level ☐ TOC				
S		in. to	ft. and	Source	Source: Land Survey GPS Topographic Map				
1 mile		in. to	ft.						
7 WELL WATER TO BE USED AS:									
1. Domestic:		ater Supply: well ID			l Field Water Supply:				
Household	6. Dewatering: how many wells?				11. Test Hole: well ID				
Lawn & Garden	echarge: well ID								
2. ☐ Irrigation	☐ Livestock 8. ☐ Monitoring: well ID				a) Closed Loop Horizontal Vertical				
3. ☐ Feedlot	e Soil Vapor I								
4. ☐ Industrial	☐ Recovery				her (specify):				
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☐ No If yes, date sample was submitted:									
Water well disinfected? \[Yes \] No									
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter in. to ft., Diameter ft., Diameter ft.									
Casing height above land surface									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: ☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)									
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)									
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft., From ft.									
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
Grout Intervals: From ft. to ft., From ft., From ft. to ft.									
Nearest source of poss		potential source of con							
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage									
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well									
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well □ Other (Specify) □ Oil Well/Gas Well									
Direction from well? ft.									
10 FROM TO	LITHOLO		FROM		LITHO. LOG (cont.)		G INTERVALS		
			1						
			1						
			1	1					
			1						
		Notes:							
11 CONTDACTODE OD I ANDOWNEDE CEDTIFICATION. This water wall was a second secon									
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year)									
Kansas Water Well	Kansas Water Well Contractor's License No								
under the business name of									
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.									
	th and Environment, Bureau of V dheks.gov/waterwell/index.html		OU SW Jacks	on St., Suite 420,	10peka, Kansas 66612-13		2785-296-3565. SA 82a-1212		
v isit us at mtp://www.k	ancks.gov/waterwen/index.html					17.5	11 1 02a-1212		