KOLAR Document ID: 1569427

	WELL R			WWC-5		vision of Wat						
		Correction		e in Well Use		ources App.]	-		Well ID			
1 LOCATION OF WATER WELL: Fraction						Section Number Township Number Range Number				0		
County: 1/4 1/4 1/4												
						treet or Rural Address where well is located (if unknown, distance and						
Business: di: Address:						irection from nearest town or intersection): If at owner's address, check here:						
Address:												
City:			State:	ZIP:								
3 LOCAT	E WELL	4.000					_					
4 DEPTH OF COMPLETED WELL:												
SECTIC	SECTION BOX: Depth(s) Groundwater Encountered: 1)					——————————————————————————————————————						
1	2) ft. 3) ft., or 4)											
				yr)			Latitude/Longitude unit make/model:		`			
NW	NE			yr)			WAAS enabled?					
	NE	Pump test d					Survey		0)			
w X	Е	-	hours				Mapper:					
		Well water was ft.										
Sw				s pumping	6 Flow	6 Elevation & Crowd Level TOC						
			Estimated Yield:gpm			6 Elevation:ft. □ Ground Level □ TOC Source: □ Land Survey □ GPS □ Topographic Map						
	S	Bore Hole I	Bore Hole Diameter: in. to			Source	Other					
	nile	DE LIGED		in. to	п.			Other	•••••			
7 WELL WATER TO BE USED AS:												
1. Domestic	1. Domestic: 5. □ Public Water Supply: well ID □ Household 6. □ Dewatering: how many wells?											
	□ Lawn & Garden 7. □ Aquifer Recharge: well ID											
	Livestock 2. Monitoring: well ID						12. Geothermal: how many bores?					
2. 🗌 Irrigati								Loop Horizont				
3. \Box Feedlo						b) Open Loop Surface Discharge Inj. of Water						
	4. Industrial Recovery Injection						13. Other (specify):					
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:												
Water well disinfected? \square Yes \square No												
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded												
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.												
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
□ Steel □ Stainless Steel □ PVC □ Other (Specify)												
□ Brass □ Galvanized Steel □ None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)												
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)												
				n ft. to								
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft. to ft.												
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other												
Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.												
	rce of possibl			potential source of cont					.1 0			
☐ Septic ☐ Sewer			Lateral Line Cess Pool	es 🗌 Pit Privy 🗌 Sewage Lag		Livestock Po Fuel Storage			cide Storage			
	ight Sewer Lir		Seepage Pit			Fertilizer St			ll/Gas Well	wen		
						i erunzei St	Jiage		ii/ Gas WEll			
				Distance from we				ft				
10 FROM	TO		ITHOLO		FROM	ТО		HO. LOG (cont.) or		G INTERVALS		
				-		-						
					1							
					Notes:							
11 CONT	RACTOR'S	OR LANDO	OWNER'S	S CERTIFICATION	: This wate	r well was		onstructed, 🗌 reco	onstructed,	or 🗌 plugged		
under my j	urisdiction ar	nd was compl	eted on (n	no-day-year)	and	this record	is tru	e to the best of m	y knowled	ge and belief.		
Kansas Wa	ter Well Con	tractor's Lice	ense No	This Wa	ter Well Red	cord was co	mple	ted on (mo-day-ye	ear)			
under the b	usiness name	01	WATED I	ELL OWNED and rate of		ondo E- CA	5 00 0					
KS Departr	Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.											
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone /85-296-3565. Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212												