KOLAR Document ID: 1592732

	WELL R			WWC-5 te in Well Use			on of Wate				
						irces App. No. With With With With With With With With			Well ID	aa Numbar	
1 LOCATION OF WATER WELL: County:						sectio	T S R			ige Number	
		$\frac{1}{4}$ TSREWreet or Rural Address where well is located (if unknown, distance and									
2 WELL Business:		rection from nearest town or intersection): If at owner's address, check here:									
Address:	direction fro	rection from nearest town or intersection): If at owner's address, check here:									
Address:											
City:			ZIP:								
3 LOCAT		C.									
				IPLETED WELL:		. ft.	5 Latitude:(decimal degr				
SECTIO	N BOX:		Encountered: 1) ft.			Longitude:					
Ν	1	2) ft. 3) ft., or 4) Dry V WELL'S STATIC WATER LEVEL:					Datum: 🗌 WGS 84 🔲 NAD 83 🔲 NAD 27				
		below land surface, measured on (mo-day-yr)							Latitude/Longitude:		、 、
NW	NE	above land surface, measured on (mo-day-yr)					☐ GPS (unit make/model: (WAAS enabled? ☐ Yes ☐ No)				
N W	NE	Pump test data: Well water was ft.					\square Land Survey \square Topographic Map			10)	
w	V E	after hours pumping gpm					□ Online Mapper:				
	<u> </u>	Well water was ft.									
SW	SE	after	after hours pumping gpn								
		Estimated Y		6 Elevation:ft. Ground Level T							
	S	Bore Hole Diameter: in. to				Source: Land Survey GPS Topographic					
1 n			in. to			. Other					
7 WELL WATER TO BE USED AS: 1. Domestic: 5. Public Water Supply: well ID 10. Oil Field Water Supply: lease 											
1. Domestic:											
			7. ☐ Aquifer Recharge: well ID 3. ☐ Monitoring: well ID				Cased Uncased Geotechnical				
	6				thermal: how many bores?						
2. □ Irrigation 9. Environmental R 3. □ Feedlot □ Air Sparge				Remediation: well ID			a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water				
				Recovery Distriction			13. \Box Other (specify):				
Was a chemical/bacteriological sample submitted to KDHE? \Box Yes \Box No If yes, date sample was submitted:											
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded											
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
I I PE OF SCREEN OR PERFORATION MATERIAL: Steel PVC Other (Specify)											
Brass Galvanized Steel None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
□ Continuous Slot □ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify)											
	red Shutter	Key Puncl					ie (Open H		ould (speeny)		
				n ft. to					ft From	ft. to	ft.
				n ft. to							
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other											
		e contaminati		potential source of con							
Septic 7			Lateral Line				vestock Pe	ens	Insection	ide Storage	
Sewer I	Lines		Cess Pool	Sewage La	agoon		el Storage		Abando	oned Water	Well
	ght Sewer Lin		Seepage Pit			🗌 Fe	rtilizer Sto	orage	🗌 Oil We	ll/Gas Well	
Direction from well? ft.											
					1						
10 FROM	TO	I	ITHOLO	GIC LOG	FROM		ТО	LIT	HO. LOG (cont.) or	PLUGGIN	G INTERVALS
ļļ											
ļļ											
ļļ											
ļļ					Notes:						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year)											
under my ju	tor Wall Car	tractor's Line	eted on (n	no-day-year) 	a	na thi	s record	1s tru	ted on (mo day and	y knowled	ge and belief.
nansas Wa	usiness name	nacior s Lice	ense ino	1 his W	ater well I	lecor	u was coi	mpie	aeu on (mo-day-ye	ar)	•••••
		Send one copy to	WATER W	ELL OWNER and retain	one for your	record	s. Fee of \$ ⁴	5.00 f	or each constructed we	<u></u> 11.	
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.											
-		ks.gov/waterwel						-			SA 82a-1212