1 LOCATION OF WATER WELL:	FRACTION	Water Well Reco	rd. Form WWC-5	KSA 82a-1212 Section Number	T bin Wanakan	D-mar Namahan	
		CP 44	CP 1/4		Township Number	Range Number	
Sedgwick Distance and direction frem nearest town or ci	SE 1/4		SE 1/4	11	т <b>27</b> s	R 2E E/W	
1415 N. 143rd E		-					
	KIN, Jean	a,Kansas					
	5 N. 143rd	Tr.			Board of Agriculture, Di	ivivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:						r:	
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:							
AN "X" IN SECTION BOX:	Depth(s) groundw		1	ft.	2 ft.	3 ft.	
	WELL'S STATIC W		_		FACE MEASURED ON mo/day/yr	05/27/1993	
Pump test data: Well water was							
	Est. Yield		water was		fter hours pum	. 9 Pr	
w E	Bore Hole Diameter	12 in.	to 80	ft.,	and in.	to ft.	
"	WELL WATER TO I		5 Public water	_		njection well	
l ≝ - sw - sæ	1 Domestic	3 Feedlot	6 Oil field wa			ther (Specify below)	
Sw SE 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was							
S	submitted			Wate	r Well Disinfected? Yes	X No	
5 TYPE OF CASING USED:		5 Wrought iron		Concrete tile		lued X Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cem	ent 9	Other (Specify bel	•	/elded	
2 PVC 4 ABS		7 Fiberglass	S	DR-26	T	hreaded	
Blank casing Diameter 5	in. to 30	ft., Dia	in.		ft., Dia in.	to ft.	
Casing height above land surface 1	,	weight	2.35		Vall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORA	TION MAI ERIAL:	5 Fiberglass		RMP (SR)	10 Asbestos-ceme		
(Ferry)							
2 Note used (open note)							
SCREEN OR PERFORATION OPENING ARE:  1 Continous slot 3 Mill slot			5 Gauzed wrapped		8 Saw cut 11 None (open hole) 9 Drilled holes		
27 marsh later and the second							
SCREEN DEDECDATION INTERVALS: 6 20						α.	
SCREEN-PERFORATION INTERVALS: from 30			t. to 80	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24		_	t. to 1t. to 80	ft., From ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: From 24			ft. to ft., From		ft. to ft. to	ft. ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					- Att		
Grout Intervals: From 4 ft. to 24 ft., From		ft.		ft., From	ft. to ft.		
What is the nearest source of possible contamination:		24., 2	•			bandon water well	
1 Septic tank 4 Later	al lines	7 Pit privy	7 Pit privy			oil well/Gas well	
2 Sewer lines 5 Cess	pool	8 Sewage lag	8 Sewage lagoon		r storage 16 O	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feed				13 Insecticide storage None A		Apparent	
Direction form well?  How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 3 topsoil				<u> </u>			
3 17 clay	_						
17 31 brown sh				+			
31 80 grey sha	le			+			
				+ +			
				<del>                                     </del>			
				<del>                                     </del>			
						4.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No							
Under the business name of Harp Well & Pump Service, Inc. by (signature) and the derick							
485							