


1 LOCATION OF WATER WELL: County: <u>Sedgewick</u>		Fraction <u>NE 1/4 SW 1/4 NE 1/4</u>	Section Number <u>17</u>	Township Number T <u>27</u> S	Range Number R <u>2</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1/2 m west of well on Central - 1/2 N in Lake Point</u>					
2 WATER WELL OWNER: <u>Morning Star Sprinkler</u> RR#, St. Address, Box #: <u>8029 So. Unread</u> City, State, ZIP Code: <u>Wichita, KS 67233</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>72</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>22</u> ft. below land surface measured on mo/day/yr <u>7/5/89</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>30</u> gpm Well water was ft. after hours pumping gpm Bore Hole Diameter <u>10</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected Yes ☒ No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) <u>2 PVC</u> 4 ABS Blank casing diameter <u>5</u> in. to ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>+12</u> in. weight <u>160</u> lbs./ft. Wall thickness or gauge No.		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>80</u> ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>80</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>20</u> ft. From ft. to ft. From ft. to ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Damage to gas line 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>DOWN SLOPE (E)</u> How many feet? <u>55+</u>			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	8	Earth			
8	15	Brownish-Red Clay			
15	45	Yellow Clay			
45	50	Yellow Broken Rock			
50	75	Yellow Clay			
75	80	Grey Shale			
		RECEIVED AUG 31 1990 DIVISION OF ENVIRONMENT			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7/5/89</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>493</u> This Water Well Record was completed on (mo/day/yr) <u>7/5/89</u> under the business name of <u>Reisner Well Drilling</u> by (signature) <u>Jerry Reisner</u>					