

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SE 1/4 NW 1/4 SE 1/4		Section Number 19		Township Number T 27 S		Range Number R 2 E	
Distance and direction from nearest town or city street address of well if located within city? 70 Feet West and 115 Feet South of the SE Corner of Sears Automotive Area, 7700 East Kellogg, Wichita, KS S-19									
2 WATER WELL OWNER: Towne East Joint Venture, c/o Melvin Simon Associates RR#, St. Address, Box #: 115 West Washington Street City, State, ZIP Code: Indianapolis, IN 46204 Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: Approximate Surface Elevation: 1347 Depth(s) Groundwater Encountered 1. 8.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 8.5 ft. below land surface measured on mo/day/yr 06/11/91 Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 20 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) Blank casing diameter 2 in. to 5 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 5 in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 5 ft. to 20 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 3 ft. to 20 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 1 ft., From 1 ft. to 3 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0.0 0.5 Asphalt 0.5 6.0 Brown Lean to Fat Clay 6.0 9.5 Brown Coarse Sand Trace Clay 9.5 20.0 Brown Lean to Fat Clay Trace Sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/11/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 07-10-91 under the business name of Terracon Consultants SC, Inc. by (signature) Steve Fischer									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									