

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE ¼ NW ¼ SE ¼	19	T 27 S	R 2 EAW
Distance and direction from nearest town or city street address of well if located within city?					
22 Feet West & 152 Feet South of SW Corner of Sears Automotive Area, 7700 East Kellogg, Wichita, KS S-23					
2 WATER WELL OWNER: Towne East Joint Venture, c/o Melvin Simon Associates RR#, St. Address, Box #: 115 West Washington Street Board of Agriculture, Division of Water Resources City, State, ZIP Code : Indianapolis, IN 46204 Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL..... 23 ft. ELEVATION: Approximate Surface Elevation:..1347.. Depth(s) Groundwater Encountered 1..... 18ft. 2.....ft. 3.....ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr ...08/06/91.. Pump test data: Well water wasft. after hours pumping gpm Est. YieldN/A.... gpm: Well water wasft. after hours pumping gpm Bore Hole Diameter..... 9in. to 23ft., and.....in. toft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a bacterial/bacteriological sample submitted to Department? Yes.....No...X..... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2in. to 13ft., Diain. toft., Diain. toft. Casing height above land surface..... -5in., weight lbs./ft. Wall thickness or gauge No. Threaded..... X					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From..... 13ft. to 23ft., Fromft. toft. GRAVEL PACK INTERVALS: From..... 11ft. to 23ft., Fromft. toft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From..... 0ft. to 9ft., From 9ft. to 11ft., Fromft. toft. What is the nearest source of possible contamination? 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0.0 0.2 Vegetation 0.2 5.5 Brown to Red-Brown Lean to Fat Clay 5.5 23.0 Brown to Olive-Brown Lean to Fat Clay With Sand Seams 23.0 25.0 Gray Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-6-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 08/10/91 by signature Steve Fischer					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					