

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NW 1/4 NW 1/4 SW 1/4		Section Number 20		Township Number T 27 S		Range Number R 2 E																															
Distance and direction from nearest town or city street address of well if located within city? 102 S. Rock Road, Wichita, KS																																							
2 WATER WELL OWNER: Fina Oil & Chemical																																							
RR#, St. Address, Box # : Box 2159						Board of Agriculture, Division of Water Resources																																	
City, State, ZIP Code : Dallas TX 75221						Application Number:																																	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 22.5 ft. ELEVATION:																																				
			Depth(s) Groundwater Encountered 1. 9.27 ft. 2. ft. 3. ft.																																				
			WELL'S STATIC WATER LEVEL 9.82 ft. below land surface measured on mo/day/yr 9/27/89																																				
			Pump test data: Well water was ft. after hours pumping gpm																																				
			Est. Yield gpm; Well water was ft. after hours pumping gpm																																				
			Bore Hole Diameter 6 3/4 in. to 25 ft., and in. to ft.																																				
			WELL WATER TO BE USED AS:																																				
			5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well																																				
			Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted																																				
			Water Well Disinfected? Yes No																																				
5 TYPE OF BLANK CASING USED:																																							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 7.5 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface Flush in., weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)																																							
SCREEN OR PERFORATION OPENINGS ARE:																																							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)																																							
SCREEN-PERFORATED INTERVALS: From 7.5 ft. to 22.5 ft., From ft. to ft.																																							
GRAVEL PACK INTERVALS: From 2.6 ft. to 25 ft., From ft. to ft.																																							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other																																							
Grout Intervals: From Surface ft. to 6 ft., From ft. to ft., From ft. to ft.																																							
What is the nearest source of possible contamination:																																							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)																																							
Direction from well? North west How many feet? 100																																							
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>12</td> <td>Silty CLAY, reddish-brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>12</td> <td>22</td> <td>Silty CLAY, light brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>22</td> <td>25</td> <td>Silty CLAY, gray green</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="6" style="text-align: center; padding: 20px;">Casing Height and Grout Variance granted</td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	12	Silty CLAY, reddish-brown				12	22	Silty CLAY, light brown				22	25	Silty CLAY, gray green				Casing Height and Grout Variance granted					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																		
0	12	Silty CLAY, reddish-brown																																					
12	22	Silty CLAY, light brown																																					
22	25	Silty CLAY, gray green																																					
Casing Height and Grout Variance granted																																							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-27-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 9-28-89 under the business name of Groundwater Technology Inc. by (signature) Bryan J. Janda																																							

2018E02068-18