

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sequoia</u>		<u>SE 1/4 NE 1/4 NE 1/4</u>	<u>21</u>	T <u>27</u> S	R <u>20</u> E
Distance and direction from nearest town or city street address of well if located within city? <u>Greenwich Central 3/4 North, West Side</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		<u>Wichita KS 67208</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>125</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>75</u> ft. 2. <u>105</u> ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>30</u> ft. below land surface measured on mo/day/yr <u>5/1/90</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>20</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>10</u> in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? <u>Yes</u> No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? <u>Yes</u> No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped			
1 Steel		5 Wrought iron		8 Concrete tile	
3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)	
2 PVC		7 Fiberglass		Welded	
Blank casing diameter <u>5</u> in. to ft., Dia				Threaded	
Casing height above land surface <u>+12</u> in., weight <u>200</u> lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel		5 Fiberglass		8 RMP (SR)	
3 Stainless steel		6 Concrete tile		11 Other (specify)	
2 Brass				12 None used (open hole)	
4 Galvanized steel				11 None (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		6 Wire wrapped		8 Saw cut	
3 Mill slot		7 Torch cut		9 Drilled holes	
2 Louvered shutter		4 Key punched		10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From <u>105</u> ft. to <u>125</u> ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From <u>20</u> ft. to <u>125</u> ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement			
		2 Cement grout			
		3 Bentonite			
		4 Other			
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		7 Pit privy		14 Abandoned water well	
4 Lateral lines		8 Sewage lagoon		15 Oil well/Gas well	
2 Sewer lines		9 Farmyard		12 Fertilizer storage	
5 Cess pool				13 Insecticide storage	
3 Watertight sewer lines				16 Other (specify below)	
6 Seepage pit					
Direction from well? <u>DOWN SLOPE</u>				How many feet? <u>75'</u>	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Earth			
8	20	red clay			
20	75	yellow clay / water			
75	105	red rock / water			
105	125	grey shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5/1/90</u> and this record is true to the best of my knowledge and belief. Kansas Water Contractor's License No. <u>493</u> This Water Well Record was completed on (mo/day/yr) <u>5/1/90</u> under the business name of <u>Rosner Well Drilling</u> by (signature) <u>Jerry Rosner</u>					