


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NW 1/4 NN 1/4 NW 1/4		Section Number 21		Township Number T 27 S		Range Number R 2 E			
Distance and direction from nearest town or city street address of well if located within city? 50' SE of Central & WEBB, WICHITA MW-5											
2 WATER WELL OWNER: RR#, St. Address, Box # : BEECH AIRCRAFT CORP 9109 E. CENTRAL City, State, ZIP Code : WICHITA, KS 67202						Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL 35 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 20 ft. 2. 20.68 ft. 3. 1-6-93 ft. WELL'S STATIC WATER LEVEL 20.68 ft. below land surface measured on mo/day/yr Pump test data: Well water was 7.25 ft. after 1-6-93 hours pumping 1-6-93 gpm Est. Yield 7.25 gpm Well water was 7.25 ft. after 1-6-93 hours pumping 1-6-93 gpm Bore Hole Diameter 7.25 in. to 7.25 ft. and 7.25 in. to 7.25 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X								
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 2 in. to 18 ft., Dia Sch 40 in. to 18 ft., Dia 18 in. to 18 ft. Casing height above land surface 0 in., weight 18 lbs./ft. Wall thickness or gauge No. 18 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 10 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) 10 SCREEN-PERFORATED INTERVALS: From 18 ft. to 28 ft., From 18 ft. to 28 ft. GRAVEL PACK INTERVALS: From 16 ft. to 35 ft., From 16 ft. to 35 ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 13 ft. to 0 ft., From 13 ft. to 16 ft., From 13 ft. to 16 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? west How many feet? 26' est											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		5		Silty Clay							
5		33		Clay - silty/sandy							
33		35		Shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-6-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 1-6-93 under the business name of Groundwater Technology, Inc. by (signature) Steven R. Mitchell											

