


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NW 1/4 NW 1/4 NW 1/4		Section Number 21		Township Number T 27 S		Range Number R 2 E	
Distance and direction from nearest town or city street address of well if located within city? 700' South of Central & WEBB, Wichita MW-4D									
2 WATER WELL OWNER: RR#, St. Address, Box # : BEECH AIRCRAFT CORP. City, State, ZIP Code : 9709 E. CENTRAL, Wichita, KS 67202					Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION: Depth(s) Groundwater Encountered dry - 999 ft. 1. ft. 2. ft. 3. 1-6-93 ft. WELL'S STATIC WATER LEVEL 7.25 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7.25 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 30 ft., Dia 5 1/2 in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight 5 1/2 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 29 ft. to 40 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 27 ft. to 0 ft., From 27 ft. to 29 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? WEST How many feet? 26 ft.									
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS			
0 1.5		Asphalt							
1.5 32		Clay & Gypsum							
32 37		Clay							
37 40		Shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-8-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 1-11-93 under the business name of Groundwater Technology, Inc. by (signature) <i>Steven R. Mitchell</i>									

