

1] LOCATION OF WATER WELL: County: SEDGWICK		FRACTION SW 1/4 SW 1/4 SW 1/4		SECTION NUMBER 21		TOWNSHIP NUMBER T 27 S		RANGE NUMBER R 2 E	
Distance and direction from nearest town or city street address of well if located within city? 700' E of WEBB & KELLOGG, WICHITA									
2] WATER WELL OWNER: BEECH AIRCRAFT CORP. RR#, St. Address, Box #: 9709 E. CENTRAL City, State, ZIP Code: WICHITA, KS 67202 Board of Agriculture, Division of Water Resources Application Number:									
3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 				4] DEPTH OF COMPLETED WELL: 43 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 36 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 36.08 ft. below land surface measured on mo/day/yr 1-6-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7.25 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X					
5] TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 33 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 0 in., weight 5 sch 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 33 ft. to 43 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 31 ft. to 43 ft., From ft. to ft. From ft. to ft., From ft. to ft.									
6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 29 ft. to 0 ft., From 29 ft. to 31 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? North How many feet? 25' int									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 1 Clayey sand 1 24 Silty clay 24 31 Silty shale 31 43 Silty clay / clayey silt									
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-7-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 1-11-93 under the business name of Groundwater Technology, Inc by (signature) Steven R. Mitchell									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Fill in blanks, underline or circle the correct answers. Send two copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									