

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		SW 1/4 SW 1/4 SW 1/4	25	T 27 S	R 2 EW
Distance and direction from nearest town or city street address of well if located within city?					Amoco #3657
200' NE of intersection of 143rd Street and Harry Street, Wichita, KS					52895097 B-2
2 WATER WELL OWNER: Amoco Corporation (Groundwater Management Section) (MW-1)					
RR#, St. Address, Box # : 7201 East 38th Street, Space 7253			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Tulsa, OK 74145			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION: Approx. Surface Elev: 1322			
N W E SW SE X		Depth(s) Groundwater Encountered 1. 35.5 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16.3 ft. below land surface measured on mo/day/yr 01/23/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7 in. to 37 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X		If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
		7 Fiberglass		Threaded X	
Blank casing diameter 2 in. to 15 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 40 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 15 ft. to 37 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 12 ft. to 37 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 9 ft. to 12 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? North		How many feet? 800			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Brown Fat Clay	0	16	Non-shrink Bentonite-Cement Grout
1	30	Gray-Green and Olive-Brown			
		Calcareous Highly Weathered Shale			
30	37	Gray Weathered Shale with Gypsum			(Casing was removed and boring re-drilled)
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/24/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 2-19-90 under the business name of Terracon Consultants, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send to three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					