

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NE 1/4 NW 1/4 SE 1/4		Section Number 25	Township Number T 27 S	Range Number R 2 E																																																												
Distance and direction from nearest town or city street address of well if located within city? 6 Miles East of Wichita																																																																		
2 WATER WELL OWNER: Charles Lougren RR#, St. Address, Box # : 1249 Brookhaven City, State, ZIP Code : Wichita, KS 67230 Board of Agriculture, Division of Water Resources Application Number:																																																																		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL . 85 ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. . . . 1.8 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL . 1.8 ft. below land surface measured on mo/day/yr 8-1 to 8-14-92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . 5 in. to . 8.6 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 8 Heat Pump Wells Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No																																																																
5 TYPE OF BLANK CASING USED: None 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass NONE Threaded Blank casing diameter . 9.99 in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface . 0-9.99 in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: None 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) NA 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) NA SCREEN-PERFORATED INTERVALS: From . . . NA ft. to . . . NA ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From . . . 0 ft. to . . . 8.5 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 <u>Watertight sewer lines</u> 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? West How many feet? 100 ft																																																																		
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>1</td><td>Top Soil</td><td></td><td></td><td></td></tr><tr><td>1</td><td>8</td><td>Red & Brown Shale</td><td></td><td></td><td></td></tr><tr><td>8</td><td>32</td><td>Red & Gray Fractured Shale</td><td></td><td></td><td></td></tr><tr><td>32</td><td>40</td><td>Gray Shale</td><td></td><td></td><td></td></tr><tr><td>40</td><td>43</td><td>Fractured Gray Shale</td><td></td><td></td><td></td></tr><tr><td>43</td><td>53</td><td>Gray Shale & Gypsum</td><td></td><td></td><td></td></tr><tr><td>53</td><td>55</td><td>Fractured Gypsum</td><td></td><td></td><td></td></tr><tr><td>55</td><td>84</td><td>Hard Gray Shale & Gypsum</td><td></td><td></td><td></td></tr><tr><td>84</td><td>86</td><td>Limestone-Very Hard</td><td></td><td></td><td></td></tr></tbody></table>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	1	Top Soil				1	8	Red & Brown Shale				8	32	Red & Gray Fractured Shale				32	40	Gray Shale				40	43	Fractured Gray Shale				43	53	Gray Shale & Gypsum				53	55	Fractured Gypsum				55	84	Hard Gray Shale & Gypsum				84	86	Limestone-Very Hard			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																													
0	1	Top Soil																																																																
1	8	Red & Brown Shale																																																																
8	32	Red & Gray Fractured Shale																																																																
32	40	Gray Shale																																																																
40	43	Fractured Gray Shale																																																																
43	53	Gray Shale & Gypsum																																																																
53	55	Fractured Gypsum																																																																
55	84	Hard Gray Shale & Gypsum																																																																
84	86	Limestone-Very Hard																																																																
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-14-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 8-19-92 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson																																																																		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																		