

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction: NW 1/4 NW 1/4 NW 1/4	Section Number: 29	Township Number: T 27 S	Range Number: R 2 E
Distance and direction from nearest town or city street address of well if located within city? 8001 E. Kellogg, Wichita, KS					
2 WATER WELL OWNER: RR#, St. Address, Box #: City, State, ZIP Code:		Amoco Corporation 7101 E. Kellogg, 38th St., Space 7253 Tulsa, OK 74102 Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 12.6 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 12.5 ft. below land surface measured on mo/day/yr 6/6/89 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No: X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No: X			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded: X Blank casing diameter in. to 8.5 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface in., weight 2 lbs./ft. Wall thickness or gauge No. Sch. 40			
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 0 ft. to 18.5 ft., From ft. to ft. From 0 ft. to 6 ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 6 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? West How many feet? 90			
FROM TO		LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
0 14		Brown Silty Clay			
14 18.5		Brown Sandy Clay			
casing height and grout variances granted.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 6-5-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 446 This Water Well Record was completed on (mo/day/yr) 6/30/89 under the business name of Downland Technical by (signature) <i>Downland</i>					