

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4	35	T 27 S	R 2 E
2 Distance and direction from nearest town or city street address of well if located within city? 2 miles South & 2 miles West of Andover					
3 WATER WELL OWNER: Tom Henna		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 14270 E. Pawnee		Application Number:			
City, State, ZIP Code: Wichita, KS 67230					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 1.0 ft. 2. 1.0 ft. 3. 1.0 ft.			
		WELL'S STATIC WATER LEVEL 1.0 ft. below land surface measured on mo/day/yr 6-15-94			
		Pump test data: Well water was 20-40 gpm. Well water was 20-40 gpm. hours pumping 20-40 gpm.			
		Est. Yield 20-40 gpm. Well water was 20-40 gpm. hours pumping 20-40 gpm.			
		Bore Hole Diameter 8 in. to 75 ft. and 75 in. to 75 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped X			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded					
Blank casing diameter 5 in. to 65 ft. Dia 5 in. to 65 ft. Dia 5 in. to 65 ft.					
Casing height above land surface 12 in. weight 2.37 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 65 ft. to 75 ft. From 65 ft. to 75 ft.					
GRAVEL PACK INTERVALS: From 25 ft. to 75 ft. From 25 ft. to 75 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 5 ft. to 25 ft. From 5 ft. to 25 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? South		How many feet? 75ft			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Top Soil			
4	7	Brown Clay			
7	20	Red & Gray Shale			
20	60	Gray Shale			
60	70	Gray Fractured Shale			
70	72	Limestone			
72	73	Cavity-Water Vein			
73	75	Limestone			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-15-94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 7-17-94					
under the business name of Peterson Irrigation Inc. by (signature) <i>Mike Peterson</i>					