

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sedgwick		SE 1/4 NE 1/4 NW 1/4		36		T 27 S		R 2E E/W	

Distance and direction from nearest town or city street address of well If located within city?

1761 Butternut Wichita, Kansas

2	WATER WELL OWNER:	GOOD, Mike
	RR#, ST. ADDRESS, BOX #:	1761 Butternut
	CITY, STATE, ZIP CODE:	Wichita, Kansas

Board of Agriculture, Division of Water Resource

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4	DEPTH OF COMPLETED WELL		75	ft.	ELEVATION:	
	Depth(s) groundwater Encountered	1		ft.	2	ft.
	WELL'S STATIC WATER LEVEL	20	FT. BELOW LAND SURFACE MEASURED ON			mo/day/yr
						06/21/1993

Pump test data:		Well water was		ft.	after	hours pumping	gpm
Est. Yield	gpm:	Well water was		ft.	after	hours pumping	gpm
Bore Hole Diameter	12	in.	to 75	ft. ,	and	in. to	ft.
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well	
1 Domestic	3 Feedlot	6 Oil field water supply		9 Dewatering		12 Other (Specify below)	
2 Irrigation	4 Industrial	7 Lawn and garden only		10 Monitoring well			

Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted _____

Water Well Disinfected? Yes ☒ No ☐

5	TYPE OF CASING USED:
---	----------------------

1 Steel	3 RMP (SR)	5 Wrought iron	6 Concrete tile	7 Fiberglass	8 Asbestos-cement	9 Other (Specify below)	10 Asbestos-cement	11 other (specify)	12 None used (open hole)
2 PVC	4 ABS	6 Asbestos-Cement	7 Fiberglass	8 RMP (SR)	9 ABS	10 Asbestos-cement	11 other (specify)	12 None used (open hole)	
Blank casing Diameter		5 in.	to	25 ft.	Dia	in.	to	ft.	
Casing height above land surface		12 in.		weight	2.35 lbs. / ft.	Wall thickness or gauge No.			.214
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel	3 Stainless Steel	5 Fiberglass	6 Concrete tile	7 Fiberglass	8 RMP (SR)	9 ABS	10 Asbestos-cement	11 other (specify)	12 None used (open hole)
2 Brass	4 Galvanized steel	6 Concrete tile	7 Fiberglass	8 RMP (SR)	9 ABS	10 Asbestos-cement	11 other (specify)	12 None used (open hole)	

SCREEN OR PERFORATION OPENING ARE:

1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)

SCREEN-PERFORATION INTERVALS:	from 25	ft. to 75	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:	from 24	ft. to 75	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 4	ft. to 24	ft. From	ft. to	ft. From
					ft. to

What is the nearest source of possible contamination:			10 Livestock pens			14 Abandon water well		
1a, From	1b, To		11 Fuel storage	12 Fertilizer storage	13 Insecticide storage	15 Oil well/Gas well	16 Other (specify below)	
1 Septic tank	4 Lateral lines	7 Pit privy						
2 Sewer lines	5 Cess pool	8 Sewage lagoon						
3 Watertight sewer lines	6 Seepage pit	9 Feedyard						

Direction from well? **South** **How many feet?** **12**

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/21/1993 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/30/93 Under the business name of Harp Well & Pump Service, Inc. by (signature) [Signature]

Jane Frederick