

1 LOCATION OF WATER WELL:		Fraction <u>NE SW SE NE</u>		Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>3/4 1/4 1/4 1/4</u>		<u>14</u>	<u>T 27S S</u>	<u>R 2E E/W</u>
Distance and direction from nearest town or city street address of well if located within city: <u>14200 Donegal Circle</u>						
2 WATER WELL OWNER: <u>David J. Brown</u>				RECEIVED SEP 06 '94 Board of Agriculture, Division of Water Resources Application Number:		
RR#, St. Address, Box # : <u>14200 Donegal Circle</u>						
City, State, ZIP Code : <u>Wichita, Kansas 67230</u>						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>60</u> ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL <u>24</u> ft. below land surface measured on mo/day/yr <u>8-17-94</u>				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter <u>9 1/2</u> in. to ft. and in. to ft.				
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial ⑦ Lawn and garden only 10 Monitoring well				
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes <u>X</u> No						
5 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped ② PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded						
Blank casing diameter <u>5</u> in. to <u>20</u> ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface <u>24"</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR26</u>						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped ⑧ Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From <u>20</u> ft. to <u>60</u> ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>60</u> ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ③ Bentonite 4 Other						
Grout Intervals: From <u>4</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage						
Direction from well? How many feet?						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
GL	5	Soil				
5	35	Clay & shale				
35	40	Shale w/lime stks				
40	60	Shale w/chert				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-17-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>171</u> This Water Well Record was completed on (mo/day/yr) <u>8-19-94</u> under the business name of <u>G & S Drilling</u> by (signature) <u>[Signature]</u>						