

1 LOCATION OF WATER WELL:	FRACTION	Section Number	Township Number	Range Number
Sedgwick SE	SW 1/4 NW 1/4 NE 1/4	14	T 27 S	R 2E E/W

Distance and direction from nearest town or city street address of well if located within city?

1201 St. Andrews Wichita, Kansas

2 WATER WELL OWNER:	WOODMAN, K.T.	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #:	1201 St. Andrews	Application Number:
CITY, STATE, ZIP CODE:	Wichita, Kansas	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 09/14/1994 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 80 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:
1 Steel	6 Asbestos-Cement	9 Other (Specify below)	Glued X Clamped
2 PVC	7 Fiberglass	SDR-26	Welded
3 RMP (SR)			Threaded
4 ABS			
Blank casing Diameter 5 in. to 30 ft., Dia	in. to ft., Dia	in. to ft.	
Casing height above land surface 12 in., weight 2.35 lbs. / ft.	lbs. / ft.	Wall thickness or gauge No. .214	
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 other (specify)
1 Steel	6 Concrete tile	9 ABS	12 None used (open hole)
2 Brass			
3 Stainless Steel	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
4 Galvanized steel	6 Wire wrapped	9 Drilled holes	
SCREEN OR PERFORATION OPENING ARE:	7 Torch cut	10 Other (specify)	
1 Continuous slot			
2 Louvered shutter			
3 Mill slot			
4 Key punched			
SCREEN-PERFORATION INTERVALS:	from 30 ft. to 80 ft., From	ft. to ft.	
GRAVEL PACK INTERVALS:	from 24 ft. to 80 ft., From	ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 24 ft. From	ft. to ft.	ft. to ft.	ft. to ft.	ft. to ft.
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandon water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	None Apparent		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				

Direction from well?	How many feet?
FROM TO LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 3 topsoil	
3 6 clay	
6 45 brown shale	
45 61 limestone	
61 70 grey shale	
70 74 limestone	
74 79 grey shale	
79 80 limestone	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/14/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/16/94
Under the business name of Harp Well & Pump Service, Inc.	by (signature) Jane Frederick