1 LOCA	ATION OF W	ATER WELL:	FRACTION	Water Well Reco	ord Form WWC-:	Section Number	Township Number	Range Number
Sedgwick NW		NW 1/4	SE 1/4	SE 1/4	10	T 27 s	25	
Distance and direction frem nearest town or city street address of well if located within city?								
1520 Woodridge Wichita, Kansas								
	TER WELL			<u>a, Kansas</u>	<del></del>	- Vinda		
	ST. ADRESS	HUMOL	S, Butch				Decard of Academitsus D	habitalan of Water Bassins
1	Y, STATE, ZII		Woodridge					vivsion of Water Resource
			ta, Kansa		05		Application Number	:
2000	" IN SECTIO			MPLETED WELL			EVATION:	
1 .	Γ	N	Depth(s) groundw		1	ft.	2 ft.	3 ft.
1 1			VELL'S STATIC W		. •		RFACE MEASURED ON mo/day/yr	09/13/1994
l '	<b>NW</b>	NE	Pump tes		water was		after hours pum	Sr
골	i		st. Yield	<b>61</b>	water was	ft.	after hours pum	ping gpm
M Mile	/		ore Hole Diameter	12 in.	to 85	ft.	and in.	to ft.
			ELL WATER TO		5 Public wate		•	njection well
lт	sw		1 Domestic	3 Feedlot	6 Oil field wa			ther (Specify below)
1 1			2 Irrigation	4 Industrial	7 Lawn and g		10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No 🗶 ; If yes, mo/day/yr sample was								
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded							'elded	
2 PVC 4 ABS 7 Fiberglass SDR-26 Threaded								
Blank c	asing Dian	ieter 5 ir	n. to 40	ft., Dia	in.		ft., Dia in.	to ft.
Casing	helght abo	ve land surface 12	in.,	weight			Wall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Ste	el	3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify	)
2 Bra	58	4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (op	en hole)
SCREE	EN OR PE	RFORATION OPEN	ING ARE:	5 Gau	ized wrapped		8 Saw cut	11 None (open hole)
1 Conti	nous slot	3 Mill slot			e wrapped		9 Drilled holes	
2 Louve	ered shutte	r 4 Key pund	ched	7 Tors	ch ent		10 Other (specify)	
SCREE	N-PERFO	RATION INTERVA	LS: from 40		t. to 85	A F		ft.
						ft., From		
	from  GRAVEL PACK INTERVALS: from 24			ft. to ft. to 85		ft., From		ft.
GRAVEL PACK INTERVALS: from 24			ft. to		ft., Fron ft., Fron		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals: From A 8 to 2 A								
		t source of possible co		IL From	IL.	10 Llvesto	ft. From ck nens 14 A	ft. to ft.   bandon water well
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel sto	177		
2 Sewer lines 5 Cess pool			8 Sewage lagoon			130	15 Oil well/Gas well 16 Other (specify below)	
I				0 0	,001		cide storage	ther (specify below)
o seepage pit 7 receivard								
Direction from well? Fast How many feet? 80 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							WATE	
	3	topsoil	INCLOSIC LOG		FROM	ТО	PLUGGING INTER	VALS
0 3	11	clay						
11	61	brown sha	10					***************************************
61		PIIG TIMOTE			<del></del>			
× +			•					
	85	grey shal	e					
			е					
			e					
			•					
			<b>e</b>					
			•					
			•					
7 COM	85 VTRACTO	grey shal	CERTIFICATION: Thi	s water well was	(1) construct	ed, (2) reconstru	icted, or (3) plugged under m	y jurisdiction and
was co	85 TRACTO	grey shal	CERTIFICATION: Thi	1994	and this rec	ord is true to the	icted, or (3) plugged under m e best of my knowledge and	belief. Kansas Water
was co Well C	NTRACTO ompleted contractor	R'S OR LANDOWNER'S on (mo/day/year)	certification: Thi	1994 This Water Well F	and this rec Record was c	ord is true to the	e best of my knowledge and bolday/yr)	belief. Kansas Water
was co Well C	NTRACTO ompleted contractor	grey shal	certification: Thi	1994 This Water Well F	and this rec Record was c	ord is true to the	e best of my knowledge and bolday/yr)	belief. Kansas Water